Multilayer network simplification: approaches, models and methods

Roberto Interdonato^a, Matteo Magnani^b, Diego Perna^c, Andrea Tagarelli^c, Davide Vega^b

^aCIRAD & UMR Tetis, Montpellier, France ^bInfoLab, Dept. of Information Technology, Uppsala University, Sweden ^cDIMES Dept., University of Calabria, Rende (CS), Italy

Abstract

Multilayer networks have been widely used to represent and analyze systems of interconnected entities where both the entities and their connections can be of different types. However, real multilayer networks can be difficult to analyze because of irrelevant information, such as layers not related to the objective of the analysis, because of their size, or because traditional methods defined to analyze simple networks do not have a straightforward extension able to handle multiple layers. Therefore, a number of methods have been devised in the literature to *simplify* multilayer networks with the objective of improving our ability to analyze them. In this article we provide a unified and practical taxonomy of existing simplification approaches, and we identify categories of multilayer network simplification methods that are still underdeveloped, as well as emerging trends.

1. Introduction

The network analysis and mining research field has raised in popularity in the last two decades, thanks to the ability of networks of representing a wide range of real-life phenomena from physical to biological and social systems, from scientific to financial data, transportation routes, and many more. In this regard, the *multilayer network model* is widely used as a powerful tool to represent the organization and relationships of complex data in many domains. Multilayer networks, which initially gained momentum in social computing [28], are designed to provide a more realistic representation of the different and heterogeneous relations that may characterize an entity in the network system. For instance, a multilayer network enables an expressive way to model different types of social relations among the same set of individuals, where layers correspond

Preprint submitted to Elsevier

March 10, 2020

Email addresses: roberto.interdonato@cirad.fr (Roberto Interdonato), matteo.magnani@it.uu.se (Matteo Magnani), d.perna@dimes.unical.it (Diego Perna), andrea.tagarelli@unical.it (Andrea Tagarelli), davide.vega@it.uu.se (Davide Vega)

to different on-line as well as off-line relations (e.g., following, co-authorship, co-working relations, and so on).

However, as we already witnessed at the beginning of the data mining era. the availability of huge amounts of complex network data represents an invaluable potential but also inevitably leads to processing issues. Just think of the number of monthly active users for the main online social networks, which is, at the time of writing, around 335 millions for Twitter¹ and more than 2billions for Facebook². Modeling these networks in their entirety for analysis purposes becomes unfeasible in most cases, and focusing on limited portions of the network (e.g., related to specific phenomena or geographical areas) is likely to cause problems in the boundary specification [69, 65], i.e., the choice of which entities and relations should be included in the data. Moreover, when dealing with multilayer networks, the boundary specification problem is even amplified: in fact, we can recognize a *horizontal* boundary specification problem for each layer similar to the one observed for single-layer networks, that is, the choice of which actors to include in the network, and a *vertical* boundary specification problem [28], i.e., the problem of choosing which types of relations should be represented in the network (i.e., how many layers and with which semantics). Given these premises, it is easy to understand how most network data modeled upon real-world phenomena may be *incomplete* and/or *noisy*: in fact, relations that are supposed to be central for a specific analysis task may be missing, or hidden under a considerable amount of irrelevant information. In certain cases, the existence of the relations and their strength may not even be possible to determine with certainty, leading to probabilistic representations [104].

Several network processing techniques have been proposed to partially overcome the above problems in order to enable complex analysis tasks on very large networks. Our goal in this work is to bring order to the existing literature on approaches, models and methods for simplification tasks in multilayer *networks.* With the term "simplification" here we refer to a specific type of network manipulation that aims at *simplifying* the structure of a network. We deliberately utilize the term with quite a broad meaning, which anyway does not coincide, hence should not be confused, with the mechanism of mapping multiple edges to single edges and removing self-loops. Rather, the choice of such a broad term derives from the observation that although a significantly large amount of techniques that may be described as simplification ones have been proposed in the literature, most of them were designed to solve specific problems in different domains; by contrast, nowadays we recognize a clear need to systematize these techniques in the context of complex network data, with emphasis on the multilaver network model, yet regardless of the peculiarities of a particular application domain. Network simplification can be seen as a special case of manipulation, which also includes other tasks such as perturbation and

 $^{^{1}} https://www.statista.com/statistics/282087/number-of-monthly-active-twitter-users/$

 $^{^{2}} https://www.statista.com/statistics/264810/number-of-monthly-active-facebook-users-worldwide/$

refinement. The former includes techniques designed for altering information encoded in a network, generally for privacy reasons (such as obfuscation and encryption techniques), whereas the latter refers to methods that are conceived to infer missing relations or attributes, or to correct the information encoded in a network (e.g., based on ontological facts).

We identify three broad categories of network simplification: *selection*, *aggre-gation*, and *transformation*. Selection methods operate on a multilayer network to reduce its size by filtering or sampling subsets of nodes, edges and/or layers, according to specific features of the entities involved or predefined model characteristics to preserve. Aggregation refers to various approaches to define partitional or hierarchical grouping mechanisms that involve nodes, edges or layers such as layer-based flattening, coarsening, summarization, community detection, and positional equivalence. Transformation approaches are divided into *projection* and *graph embedding* methods. Projection methods are designed to deal with different node (entity) types in a network, and aim to replace nodes of selected types with relations. Finally, graph embedding techniques aim to transform a graph into a low-dimensional, vectorial representation, which is also key enabling for machine and deep learning tasks.

Motivations for performing a simplification task on a multilayer network are manifold and often they are raised from different requirements in the target application domain. In this regard, we can recognize the following computational aspects for which a network simplification task can be beneficial:

- By solving noise or incompleteness issues in a complex network, the relevant information contained in the network will more easily be unveiled, leading to *improved data quality*. This is expected to have a beneficial impact on the effectiveness of methods to be applied for further analysis tasks.
- Simplifying a complex network can lead to *improved performance* of further computational analysis methods which may struggle with efficiently handling very large networks.
- Simplifying a complex network can also *enable application* of an existing method originally conceived for simple (i.e., monoplex) networks, or can aid to cope with model compatibility issues when it is not possible to apply a selected method on a given network model.

Contributions. In this work, we provide the first conceptualization of the network simplification problem for multilayer networks, for which we recognize and formally define three main categories. According to this classification, we propose a formal systematization of approaches, models and methods related to network simplification tasks.

One major goal of our work is to discuss how simplification approaches that were conceived for simple networks could only be extended, adapted, or redefined to deal with multilayer networks. In this regard, whenever there is a lack in recent literature to support pursuing the above goal, we eventually try to hint at methodological solutions for specific classes of simplification techniques for multilayer networks.

Limitations and scope. In this work, we will focus on a topology-driven multilayer network model, therefore we will leave out of consideration techniques that are designed to deal with node and/or edge attributes, such as reduction of the number of attributes associated to nodes/edges in a network (e.g., feature selection methods), or reduction of the cardinality of the value set for a certain attribute (e.g., discretization, binning). We consider the above techniques closer to a traditional data mining scenario than to a network mining one, and they are often domain-specific. More details on feature selection, discretization and other methods focusing on attribute values rather than network structure can be found in most data mining and machine learning textbooks.

It should be noted that, although the focus of this work is on multilayer networks, we will also discuss how simplification techniques that are not originally conceived for multilayer networks can be applied to such networks. In this respect, we refer the reader to more focused surveys that cover one or more topics related to the ones discussed in this work but referring to single-layer networks only. For instance, Liu et al. [76] overview methodologies for static and dynamic graph summarization, which can also support related tasks, such as compression and clustering; Beck et al. [7] provides a comprehensive survey on visualization of dynamic graphs, which has also attracted increasing interest from different research communities.

Plan of this paper. The rest of the paper is organized as follows. We provide formal definitions for each of the three network simplification categories in Section 2. Accordingly, in Section 3 we classify existing methods in the literature in the context of our taxonomy and provide an overview of the main methods for each category, so that the readers can use this article to identify potentially useful approaches for their simplification problems. This overview of the literature allows us to identify categories of multilayer network simplification methods that are still underdeveloped, as well as emerging trends, as a starting point for future research. A forward-looking discussion of these and other general aspects emerging from our classification and literature review is presented in Section 4. Moreover, we review the available software implementations of methods for multilayer network analysis with emphasis on network simplification. One of the objectives of this article is indeed to boost the integration of individual methods into more general libraries and frameworks, to make them more easily usable and extensible. Finally, in Section 5, we sum up the limitations of existing methods for multilayer network simplification, and draw several pointers for future research.

2. Definitions of Network Simplification

Given a set of actors \mathcal{A} and a set of layers \mathcal{L} , a *multilayer network* is defined as a quadruple $G = (\mathcal{A}, \mathcal{L}, V, E)$ where (V, E) is a graph, $V \subseteq \mathcal{A} \times \mathcal{L}$ and $E \subseteq V \times V$. Each actor must be present in at least one layer, but each layer is not required to contain all actors. Each node in one layer could be linked

notation	description
G	multilayer network graph
\mathcal{A}	set of actors
$L; \mathcal{L}; l$	Layer; set of layers; number of layers
V	set of nodes
E	set of edges
$\wp; p$	power set function; set function
$\theta; \Theta$	expression; set of expressions
\mathcal{T}	set of string constants
$f_{ heta}$	simplification function
V_f	flattened set of nodes
E_{f}	flattened set of edges
ω, w	actor, resp. layer, weighting functions
S,C	coarsened graph, set of corrections
k	coreness vector
d	size of the embedding
\mathbf{v}_n^i	embedding vector for node n in layer L_i

Table 1: Main notation used in this paper

to nodes corresponding to the same actor in a few or all other layers; in the multiplex setting, the inter-layer links only connect the same actor in different lavers.

In the following, we provide a meta-definition of the network simplification problem, which is meant to establish a formal backbone for all simplification tasks under consideration in this work, i.e., selection, aggregation, and transformation. Table 1 shows the main notation introduced in this section.

A key constituent of our meta-definition corresponds to a function, denoted as f_{θ} , that describes the modification to a multilayer network carried out by a simplification method. Depending on the type of expressions Θ , the simplification function is further designed to support a specific simplification task. The outcome of a network simplification process is a multilayer network whereby one or more of the structural elements of the original network (i.e., $\mathcal{A}, \mathcal{L}, V$) E) are being affected by the process. Formally, this is denoted at the end of the meta-definition, as well as at the end of each of the subsequent specialized definitions, by a disjunction of conditions that declare which network elements are affected by a selection or modification of their respective sets, for each simplification category; this information is also summarized and concisely reported in the column *affected elements* of Table 2, which will be discussed later in Section 3.

Meta-Definition 1 (Network Simplification) Let $\mathcal{G}(\mathcal{A}, \mathcal{L})$ denote the set of all possible multilayer networks that can be defined over \mathcal{A} and \mathcal{L} . Moreover, let $\Theta(\mathcal{A}, \mathcal{L}, V, E)$ denote a set of expressions on alphabets $\mathcal{A}, \mathcal{L}, V, E$. Given a multilayer network $G = (\mathcal{A}, \mathcal{L}, V, E) \in \mathcal{G}(\mathcal{A}, \mathcal{L})$, expressions $\theta \subseteq \Theta(\mathcal{A}, \mathcal{L}, V, E)$, let $f_{\theta} : \mathcal{G}(\mathcal{A}, \mathcal{L}), \theta \mapsto \mathcal{G}(p(\mathcal{A}), p(\mathcal{L}))$ be a network simplification function, such



Figure 1: Illustrative example of selection-oriented simplification: the subset of actors $\{A_1, A_2, A_3\}$ and the subset of layers $\{L_1, L_2\}$ are selected from an input multilayer network (on the left).

that the set of actors $p(\mathcal{A})$ and the set of layers $p(\mathcal{L})$ in the simplified network are defined as follows: either $p(\mathcal{A}) \subseteq \mathcal{A}$ or $p(\mathcal{A}) \subset \mathcal{O}(\mathcal{A})$, and either $p(\mathcal{L}) \subseteq \mathcal{L}$ or $p(\mathcal{L}) \subset \mathcal{O}(\mathcal{L})$, where $\mathcal{O}(\mathcal{A})$ and $\mathcal{O}(\mathcal{L})$ are the power sets of actors and layers, respectively. The network simplification problem is to obtain a network $f_{\theta}(G) = G' = (\mathcal{A}', \mathcal{L}', V', E')$ such that the following disjunction of conditions holds: $|\mathcal{A}'| < |\mathcal{A}| \lor |\mathcal{L}'| < |\mathcal{L}| \lor |V'| < |V| \lor |E'| < |E|$.

Definition 1 is supposed to be specialized for each of the three simplification categories. In the *selection* case, the simplification function depends on select expressions, i.e., it is defined to identify a subset of \mathcal{A} and/or \mathcal{L} , and consequently V and/or E, as provided in the following definition. Figure 1 shows an example of selection-oriented simplification.

Definition 1 (Selection-oriented Network Simplification) Given a multilayer network graph $G = (\mathcal{A}, \mathcal{L}, V, E)$, let f_{θ} be a simplification function with $\theta \subseteq \Theta(\mathcal{A}, \mathcal{L}, V, E)$ such that Θ is a set of expressions of the form select(X), with variables $X \in \{\mathcal{A}, \mathcal{L}, V, E\}$. The Selection-oriented network simplification problem is to obtain a network $G' = (\mathcal{A}', \mathcal{L}', V', E')$, where $G \xrightarrow{f_{\theta}} G'$, s.t. $\mathcal{A}' \subset \mathcal{A} \lor \mathcal{L}' \subset \mathcal{L} \lor V' \subset V \lor E' \subset E$.

Aggregation methods are in principle characterized by the evaluation of expressions of type group-by over \mathcal{A} and/or \mathcal{L} , in order to obtain a multilayer network whose actors (resp. layers) are organized into a set of subsets induced from the original multilayer network. Note that the set of subsets of actors (resp. layers) in the simplified multilayer network is supposed to be smaller than the corresponding set in the original network; also, this reflects on the cardinality of the sets of nodes and/or edges in the resulting simplified network. An example of aggregation is shown in Figure 2.



Figure 2: Illustrative example of aggregation-oriented simplification: the set of actors is partitioned as $\{\{A_1, A_2, A_3\}, \{A_4, A_5, A_6\}, \{A_7\}, \{A_8\}\}$, and the set of layers is partitioned as $\{\{L_1, L_2\}, \{L_3\}\}$ (on the left). In the simplified network (on the right), filled circles denote meta-nodes resulting from the actor aggregation.

Definition 2 (Aggregation-oriented Network Simplification) Given a multilayer network graph $G = (\mathcal{A}, \mathcal{L}, V, E)$, let f_{θ} be a simplification function with $\theta \subseteq \Theta(\mathcal{A}, \mathcal{L}, V)$ such that Θ is a set of expressions of the form group(X), with variables $X \in \{\mathcal{A}, \mathcal{L}, V\}$. The Aggregation-oriented network simplification problem is to obtain a simplified network $G' = (\mathcal{A}', \mathcal{L}', V', E')$, where $G \stackrel{f_{\theta}}{\mapsto} G'$, s.t. $|\mathcal{A}'| < |\mathcal{A}| \lor |\mathcal{L}'| < |\mathcal{L}| \lor |V'| < |V| \lor |E'| < |E|$, where $\mathcal{A}' \subset \wp(\mathcal{A}), \mathcal{L}' \subset \wp(\mathcal{L})$.

In the case of *transformation*, we distinguish two subcategories: *embedding* and *projection*. The embedding-based transformation is characterized by a two-stage process. The first stage is to learn a low-dimensional vectorial representation (i.e., embedding) for actors and/or nodes of the input multilayer network. By exploiting the learned embeddings, an edge is defined in the simplified network whenever the distance between any two actors' (resp. nodes') embeddings does not exceed a predetermined threshold ϵ . Figure 3 shows an example of embedding-based transformation.

Definition 3 (Embedding-based Transformation-oriented Network Simplification) Given a multilayer network graph $G = (\mathcal{A}, \mathcal{L}, V, E)$, let f_{θ} be a simplification function with $\theta \subseteq \Theta(\mathcal{A}, V)$ such that Θ is a set of expressions of the form $dist(X_1, X_2, \epsilon)$, with variables $X_1, X_2 \in \kappa$ such that $\kappa = g(\mathcal{A})$ (resp. $\kappa = g(V)$), numeric constant $\epsilon \in [0, 1]$, with $g : \mathcal{A} \mapsto \mathbb{R}^d$ (resp. $g : V \mapsto \mathbb{R}^d$) with numeric constant d > 1. The semantics of $dist(X_1, X_2, \epsilon)$ is that "if the distance between X_1 and X_2 is not above ϵ then an edge is created between the actors (resp. nodes) corresponding to X_1 and X_2 ". The Embedding-based Transformation-oriented network simplification problem is to obtain a simplified network $G' = (\mathcal{A}', \mathcal{L}', V', E')$, where $G \stackrel{f_{\theta}}{\longmapsto} G'$, s.t. $\mathcal{A}' \subset \mathcal{A} \lor \mathcal{L}' \subset \mathcal{L} \lor V' \subset V$, and $E' \subseteq V' \times V'$.



Figure 3: Illustrative example of embedding-based transformation-oriented simplification: through an embedding method a new representational space is learned, in which every actor is represented by an embedding vector. In the simplified network (on the right), blue edges denote predicted edges resulting from the reconstruction process of the network through a distance measure.



Figure 4: Illustrative example of projection-based transformation-oriented simplification: given two types of actors, A and B, in the input multilayer network (on the left), projection on type B is performed (on the right). (Best viewed in color version)

The projection-based transformation aims at simplifying the multilayer network structure according to side information relating to the *type* of actors (resp. nodes) present in the network. The simplification process here consists in replacing every actor (resp. node) of a given type in \mathcal{T} , say τ , with a new edge connecting each pair of its neighboring nodes of type other than τ . When removing actors (resp. nodes) of type τ , every edge connecting the removed nodes are also removed from the resulting network. Note that the simplified network will be characterized by a subset of actors (resp. nodes) of the original network,



Figure 5: Hierarchy of network simplification approaches

a partially new set of edges, and an unchanged set of layers. Figure 4 shows an example of projection-based transformation.

Definition 4 (Projection-based Transformation-oriented Network Simplification) Given a multilayer network graph $G = (\mathcal{A}, \mathcal{L}, V, E)$, let f_{θ} be a simplification function with $\theta \subseteq \Theta(\mathcal{A}, V)$ such that Θ is a set of expressions of the form prj(X), with variables $X \in g(\mathcal{A})$ (resp. $X \in V$), and $g : \mathcal{A} \mapsto \mathcal{T}$ (resp. $g : V \mapsto \mathcal{T}$), with \mathcal{T} set of string constants. The semantics of prj(X) is that "every actor (resp. node) of type X is removed and an edge is created for each pair of its neighboring nodes of type other than X." The Projection-based Transformation-oriented network simplification problem is to obtain a simplified network $G' = (\mathcal{A}', \mathcal{L}, V', E')$, where $G \stackrel{f_{\theta}}{\mapsto} G'$, s.t. $\mathcal{A}' \subset \mathcal{A} \land |E'| < |E|$, where $E' = E^{(1)} \cup E^{(2)}$, with $E^{(1)} \subset E, E^{(2)} \subseteq V' \times V', V' \subset V$.

3. Tidying Up Network Simplification Literature

In this section we elaborate on each of the previously presented network simplification categories and relating methods existing in the literature.

Figure 5 shows our hierarchy of categories and subcategories of simplification techniques. Moreover, as a guide to our discussion, Table 2 reports on main characteristics of the approaches developed for network simplification, organized according to the above provided categorization. For each method, the table shows: the type of information which is primarily used to drive the simplification task; the network aspects affected by the process, where superscript + (resp. -) indicates that the size of a set will increase (resp. decrease) at the end of the simplification task; whether the simplification scheme is deterministic or probabilistic (regardless of possible requirements in terms of meta-structures to compute, such as node groupings or embeddings); whether the method is reversible or not, i.e., whether the original network can be fully or only partially reconstructed from the simplified one; main references for single-layer networks; and main references for multilayer networks. Note that for the two last columns, we use symbol - to denote the method does not make sense for single-layer, resp. multilayer, networks, and symbol \mathbf{X} to denote that no method has been developed yet. A \checkmark symbol has been used to denote that a well known family of techniques exists, but it is so vast that a reference list would not be exhaustive or significant. Finally, the notation E_{κ} reported for embedding-based methods represents an edge set derived from an embedding space k over \mathcal{A} or V (cf. Definition 3).

	multilayer native	[14, 123, 22, 6, 32, 131, 39, 124,	73, 136, 89, 5, 30, 29] $[114]$	[80]	[42, 60]	[129, 62, 77, 64, 24, 2, 130, 67,	103, 10, 57, 56]	I	[142, 126, 105, 101]	[28, 9]	[25]	×	×	[120, 100, 94, 98]	[75, 140, 85]
	single-layer native	>	1	[121, 110, 84, 27, 125, 41, 20]	[70, 72, 71]	[95, 23]	[51 A6 54 117 116 43 00 15	$\begin{bmatrix} 0.1, \pm 0, 0\pm, 111, 110, \pm 0, 33, 10, \\ 51, 59, 68, 38 \end{bmatrix}$	$\begin{bmatrix} [53, 36, 34, 78, 79, 138, 115, 106, \\ 107, 50, 33 \end{bmatrix}$		1	$\left \left[93, 133, 74, 1, 37, 35, 81, 76, 61, \right. \right $	$egin{array}{cccccccccccccccccccccccccccccccccccc$	>	[109, 45, 128, 48, 63, 132, 18, 135]
	reversibility	°N N	No	°Z	No	No	202		Yes	No	°Z	\mathbf{Yes}	Yes	°N N	No
	meinimrətəb	\mathbf{Yes}	Yes	\mathbf{Y}/\mathbf{N}	No.	\mathbf{Y}/\mathbf{N}	N/N	NT / T	\mathbf{Yes}	\mathbf{Yes}	$\mathbf{Y}_{\mathbf{es}}$	\mathbf{Yes}	\mathbf{Y}/\mathbf{N}	\mathbf{Yes}	\mathbf{Y}/\mathbf{N}
and the second	алетер баралан	V^-, E^-	$V^{-}.E^{-}$	$V^{-}E^{-}$	V^-,E^-	V^-,E^-	V - E -	, Ť	V^-, E^-	τ^E, V^-, E^-	$ au_{\overline{E}}^{-}, E^{-}, V^{-}$	V^{-},E^{-}	V^{-}, E^{-}	V^-, E^+	V, E_κ
	kyreyrensbling elements	Λ	Λ	V,E	V,E	V, E	5	1	E	J	7	V,E	V, E	$\mathcal{A} V,\mathcal{T} $	$\mathcal{A}(orV), \kappa$
	method	centrality-based filtering (cf. Sec. 3.1.1, p. 12)	node-laver relevance filtering (cf. Sec. 3.1.1. n. 13)	model-based filtering (cf. Sec. 3.1.1, p. 14)	sampling (cf. Sec. 3.1.2, p. 16)	community-detection-based (cf. Sec. 3.2.2, p. 20)	multilond routitioning (of Soc 2.0.2 r. 91)	munever parenteming (cr. Sec. 9.2.9, p. 21)	positional equivalence (cf. Sec. 3.2.4, p. 23)	flattening (cf. Sec. 3.2.1, p. 19)	layer aggregation (cf. Sec. 3.2.1, p. 19)	graph compression (cf. Sec. 3.2.5, p. 24)	coarsening (cf. Sec. 3.2.3, p. 21)	projection-based (cf. Sec. 3.3.1, p. 25)	embedding-based (cf. Sec. 3.3.2, p. 27)
	category		Selection					Aggregation						Transformation	

Table 2: Characteristics of network simplification methods.



Figure 6: Two portions of the AUCS network used to exemplify simplification methods. (a) Two multiplex layers with "lunch" (top) and "Facebook" (bottom) relationships between the same set of employees. (b) Two heterogeneous layers with employees (top) and research papers (bottom), with edges indicating who authored which paper.

In the following we will use a real multilayer network about a university department [114] to exemplify different simplification methods. In this network different layers are used to represent either different types of edges between the same actors, e.g., having lunch together and being friends on Facebook, or edges between different types of entities, in particular authorship relationships between employees and research papers. Figure 6 shows two combinations of layers that will be used as running examples.

3.1. Selection based techniques

We use the broad term *selection* to refer to techniques that aim to reduce the size of the input network by selecting a subset of nodes, edges, or layers, according to specific features involving the interested entities of the network. Selection techniques can be grouped into two main categories: filtering and sampling. The former includes methods that exploit selective information requirements, such as methods that employ information given by centrality measures as a selection criterion, and approaches that leverage edge statistical significance information to filter out noisy links. The latter contains approaches belonging to random-access and exploration-based categories.

3.1.1. Filtering

Filtering approaches resemble the problem of *dimensionality reduction* in relational data, in that they involve the identification and removal of a (possibly large) number of edges or nodes that are supposed to prevent the discovery of patterns due to redundancy, irrelevance, missing values, noise or other related aspects. Filtering in graphs is also commonly referred to by using different terms such as pruning, thresholding, and sparsification. In particular, thresholding refers to filtering out those edges/nodes whose value for some selected property exceeds a predefined threshold, while sparsification typically aims to approximate the input graph with a sparser one, guaranteeing that some properties of the original graph are preserved within a chosen degree of tolerance. For the sake of simplicity, in the rest of this section we will use filtering as unifying term, unless otherwise specified.

Centrality-based filtering. The basic idea underlying centrality-based filtering is to apply one of the aforementioned approaches to rank the nodes by centrality scores and, given a predetermined threshold, select those nodes in a graph that satisfy the constraint based on the threshold. The term *centrality* in networks commonly refers to importance or prominence of a node in a network, i.e., the status of being located in strategic locations within the network. There is no unique definition of centrality, as for instance one may postulate that a node is important if it is involved in many direct interactions (i.e., *degree* centrality), or if it connects two large components acting as a bridge (i.e., *betweenness* centrality), or if it allows for quick transfer of the information also by accounting for indirect paths that involve intermediaries (i.e., *closeness* centrality).

Brodka et al. propose a definition of degree centrality for multilayer networks in [14]. Sole et al. [123] define a multilayer extension of the betweenness centrality by taking into account shortest paths that include inter-layer edges. The same authors in [124] extend random walk betweenness and closeness centrality to interconnected multilayer networks. A cross-layer betweenness centrality is proposed in [22], also including applications to multilayer community detection and message spreading tasks. Two classes of multilayer degree-biased random walks are proposed in [6], to analyze to what extent this kind of random walks can make the exploration of multilayer networks more efficient. In [32], De Domenico et al. study main factors influencing the navigability of multilayer networks, using random walks over a layer-aggregated network; in general, when dealing with centrality scores produced at distinct layer networks, the use of different aggregation and normalization techniques is shown to strongly bias the final results [131]. In [30], Ding and Li define topologically-biased random walks on multiplex networks and derive analytical expressions for their long-term diffusion properties such as entropy rate and stationary probability distribution. They found that inter-layer coupling strength, edge overlapping, the sign and presence of inter-layer degree-degree correlations and the number of layers capture the extent to which the diffusions on a multiplex network are efficiently explored by a biased walk. The same authors define topologically biased multiplex PageRank in [29]. Perna et al. in [108] introduce the Alternate Lurker-Contributor Ranking method (mlALCR). By solving two mutually dependent systems of equations, mlALCR is able to identify users characterized by alternate behaviors (i.e., information-producer vs. information-consumer) across the layers of a multilayer network. Using a fourth-order tensor to represent multilayer networks, Wang and Zou [136] propose the Singular Vector of Tensor (SVT) centrality, which is used to quantitatively evaluate the importance of nodes connected by different types of links in multilayer networks, through the computation of hub and authority scores of nodes and layers in multilayer networked systems. In [5], Basaras et al. study how to identify influential information spreaders in multilayer networks, and they propose a family of measures for describing the strategic position of a node within a multilayer network, based on the connectivity of the node with respect to nodes belonging to the same layer as well as to the rest of the layers.

A related approach, which is also commonly adopted in simple graphs, is to induce an organization of the nodes into substructures with desired structural characteristics based on some notion of centrality. Within this view, an exemplay method is the *k*-core decomposition, which consists in finding cohesive subgraphs based on node degree [119]. A k-core is a maximal subgraph in which all nodes have degree at least k. The problem of core decomposition of a multilaver network is studied in [39]. Given a multilayer network $G = (\mathcal{A}, \mathcal{L}, V, E)$ and an $|\mathcal{L}|$ -dimensional integer vector $\mathbf{k} = [k_l]_{l \in \mathcal{L}}$, the multilayer k-core of G is the maximal subgraph whose nodes have at least degree k_l in that subgraph, for all layers l. Vector \mathbf{k} is the coreness vector of the k-core. The set of all non-empty and distinct multilayer cores constitutes the multilayer core decomposition of G. Nevertheless, the authors observe that with this definition the number of multilayer cores can be exponential in the number of layers, i.e., the cores are not nested into each other like in the single-layer case, rather they form a core lattice defining a relation of partial containment. As a solution, the authors propose three algorithms based on different pruning rules and visiting strategies of the lattice. In [89], Moorman et al. propose effective filtering methods for finding subgraphs isomorphic to an input template graph inside a large multiplex network by reducing the search space based on local statistics.

Examples of different types of multilayer node filtering are shown in Figure 7. In Figure 7(a) a node is kept on a layer only if the corresponding actor has a sufficient degree centrality in all layers. Notice that, as with simple networks, this approach may not preserve the degree centrality rank of the nodes: a node adjacent to a large number of nodes, none of which passes the filtering threshold, will be disconnected on the filtered network despite its high original degree. In Figure 7(b) only nodes having most of their neighbors exclusively present on a layer are preserved. From this simplification we can see how Facebook connections are in most cases replications of offline connections, and how some clusters exist in the lunch layer that would disappear if these connections had to rely on Facebook friendships.

Node-layer relevance-based filtering. Rossi and Magnani [114] define a local simplification approach in the context of a discussion about effective visualization strategies. Two variants of the approach are proposed, based on the concepts of relevance and exclusive relevance introduced in [11]. Given a node-layer pair, relevance measures the fraction of neighbors a node has in a layer, with respect to its total number of neighbors; similarly, exclusive relevance measure the fraction of exclusive neighbors with respect to a layer, i.e., neighbors a node just has in that layer. The simplification process is performed as a threshold-based



Figure 7: The "lunch" and "Facebook" layers in the AUCS networks filtered according to (a) neighborhood, in particular, preserving only nodes with at least six neighbors in both layers, and (b) exclusive layer relevance greater than .6, indicating that at least 60% of the actor's neighbors on that layer are only present on that layer.

filtering of the edges in the network: given a threshold, for each layer, only edges between nodes with a relevance value above the threshold in that layer are kept in the network. Compared to other simplification approaches for multilayer networks, this approach has the advantage of preserving the full information about the original layers. However to the best of our knowledge this approach has not been tested on real applications, therefore there is still limited evidence regarding its effectiveness.

Model-based filtering. A relatively recent corpus of study addresses the task of filtering out "noisy" edges from complex networks based on *generative null models*. The general idea is to define a null model based on edge distributions, use it to compute a *p*-value for every edge (i.e., to determine the statistical significance of properties assigned to edges from a given distribution), and finally filter out all edges having *p*-value above a chosen significance level, thus keeping all edges that are least likely to have occurred due to random chance.

Methods following the above general approach have been mainly conceived to deal with weighted networks, so that both the node degree and node strength (i.e., the sum of the weights of all incident edges) are used to generate a model that defines a random ensemble of graphs resembling the observed network. One of the earliest methods is the *disparity filter* [121], which evaluates the strength and degree of each node locally. The null hypothesis is that the strength of a node is redistributed uniformly at random over the node's incident edges. The disparity filter hence introduces some bias in that the strength of neighbors of a node are discarded. By contrast, a global null model is defined with the *GloSS filter* [110], as it preserves the whole distribution of edge weights within a single graph. The null model is in fact a graph with the same topological structure of the original network and with edge weights randomly drawn from the empirical weight distribution. Since all edges have the same probability of being assigned a given weight, the statistical test is the same for every edge, and hence this reduces to setting a global threshold (depending on a chosen significance level) for pruning. Unlike disparity and GloSS, the null model proposed by Dianati [27] is maximum-entropy based and hence unbiased. Upon it, two filters are defined: the marginal likelihood filter, which is a linear-cost method that assigns a significance score to each edge based on the marginal distribution of edge weights, and the global likelihood filter, which is an ensemble approach that accounts for the correlations among edges. Both filters consider the strength of nodes, but not the degrees. Recently, Gemmetto et al. [41] proposed a maximum-entropy filter that guarantees that only irreducible edges are kept, i.e., the filtered network will retain only the edges that cannot be inferred from local information. The general goal is to unveil the backbone of non-redundant structures in a complex network. The proposed filter employs a null model based on the canonical maximum-entropy ensemble of weighted networks having the same degree and strength distribution as the real network [84], which allows to overcome redundancy issues that arise in the aforementioned filters. On a similar research direction is the unbiased method proposed in [125], which combines an exact maximum-likelihood approach with an efficient computational sampling scheme to sample ensembles of various types of networks (i.e., directed, undirected, weighted, binary) with many possible constraints (degree sequence, strength sequence, reciprocity structure, mixed binary and weighted properties, etc). The generalized hypergeometric ensembles (gHypE) framework proposed in [20] focuses instead on inferring significant links in relational data, by providing an analytically tractable statistical model of directed and undirected multi-edge graphs. It can also account for known factors that influence the occurrence of interactions, such as known group structures, similarities between elements, or other forms of biases.

Some of the above generative models for graph pruning have been recently used in the context of *consensus community detection* in multilayer networks [80]. Essentially, a generative null model is evaluated on a *weighted graph of coassociations* (or co-occurrences): given an input multilayer network and an ensemble of layer-specific community structures defined over it, a weighted coassociation graph is an undirected graph whose nodes correspond to the actors/entities in the multilayer network and the strength of an edge corresponds to the fraction of communities that two entities share in the ensemble community structures. The key idea adopted in [80] is that a relatively low value of co-association might be retained as meaningful provided that it refers to node relations that make sense only for certain layers; by contrast, a relatively high value of co-association could be discarded if it corresponds to the linkage of nodes that have high degree and co-occur in the same community in many layers, and hence the co-association could be considered as superfluous in terms of community structure.

3.1.2. Sampling

When dealing with the analysis of real-world complex networks, it is likely to incur in scalability issues. In these cases, a popular solution is to perform the analysis on a smaller sample of the network. With the term *network sampling* we will refer to all the techniques which aim at obtaining a (relatively small) representative sample from a network, i.e., a subset of nodes and edges partially preserving structural characteristics of the original network. Sampling can also be thought as a valid alternative to synthetic graph generation [66], i.e., instead of growing a synthetic graph with a set of desired properties, in some cases it can be preferable to shrink the original graph to a smaller size maintaining the main structural properties.

It should be noted that while network sampling and graph compression (cf. Section 3.2.5) are often used to refer to similar methods in literature, in this work we will consider as *network sampling* all the techniques based on stochastic/random processes (i.e., non-deterministic techniques), while techniques which include deterministic procedures allowing reversibility or recoveryrate of the process will be considered in the graph compression category.

While the most common scenario is that of a scale-down goal (i.e., obtaining a sample showing similar properties as compared to the original graph), the effectiveness of a sampling process may also be evaluated considering a back-intime goal, i.e., when the aim is to obtain a sample similar to what the original graph looked like when it was the size of the sample [71].

Sampling techniques can be categorized based on the way they access the graph during the sampling process, i.e., random access based techniques or exploration based techniques. While the former envisages a local approach, the latter includes all the approaches which take into account broader information about the graph structure. In the following, we provide an overview of main sampling approaches for each category.

Random access techniques. An intuitive way to sample a graph is to perform a random selection process, i.e., fixed a size n for the sample, uniformly select n nodes (or n edges) at random and build their induced subgraph [71]. Nevertheless, sampled graphs obtained using this technique do not retain basic graph properties, e.g., random subnets sampled from scale-free networks are not themselves scale-free [127]. Non-uniform selection criteria can also be used, e.g., nodes may be selected based on their degree or PageRank score. Hybrid strategies have also been proposed, based on random selection of both nodes and edges. In the random node-edge sampling [71], at each step a node is randomly selected, and then one of its neighbors is randomly selected. Random edge-node sampling [111] starts by selecting a set of random edges, then an induced graph is built by adding all the neighbors of the nodes connected to the original set of random edges. Random access techniques generally lead to degree distribution and sparse connectivity problems [71]. While their applicability is guaranteed also on multilayer networks (e.g., performing global or layer-wise random processes), these drawbacks are even emphasized in this scenario, where a random selection may also create a strong population and connectivity unbalance among

the different layers.

Exploration-based techniques. Advanced sampling techniques have been proposed in order to overcome the problems coming from random access based approaches, introducing solutions that allow to partially maintain some characteristic of the original network, e.g., network connectivity and degree distribution. Nevertheless, while consolidated approaches exist for simple graphs, sampling of multilayer networks can be considered an open problem, since few techniques have been proposed that are specifically conceived for these models.

Exploration based techniques (also referred to as topology-based or traversalbased) for simple networks, are generally based on the idea to first select a node uniformly at random and then explore its neighborhood. A well known example of this strategy is the snowball sampling, which adds nodes and edges using breadth-first search from a randomly selected seed node. While the network connectivity is maintained within the snowball, many peripheral nodes (i.e., those sampled on the last round) will be missing a large number of neighbors, causing the so-called *boundary bias* phenomenon [70]. Another well known exploration strategy is the random walk based one proposed in [71], that works by picking a starting node uniformly at random, and then sampling the graph by simulating a random walk on it. Sampling techniques based on temporal graph evolution have also been defined, e.g., Forest Fire sampling [72]. The idea is to randomly pick a seed node and begin "burning" outgoing links and the corresponding nodes, based on two input parameters called forward and backward burning probability. The process goes on recursively starting from the endpoints of the burned links, until convergence (as the process continues, nodes cannot be visited a second time, preventing infinite loops).

As regards sampling approaches for multilayer networks, an early approach has been proposed by Gjoka et al. [42] in the context of online social networks. They observe that, when dealing with online social network graphs, random walk based sampling can produce representative samples only if the social graph is fully connected. To solve this problem, they propose to take into account multiple social interactions happening in a social network, in order to have higher chances to obtain a fully connected *union* graph, i.e., a single-layer network built by taking into account all possible relation types. To further improve upon the sampling process, they then propose a layer-wise random walk based sampling. which seems to outperform standard techniques on the obtained *multigraph*. The idea is to perform a two-stage random walk based sampling, where the first stage consists in selecting a relation type on which to walk (i.e., a layer), and the second one in enumerating the neighbors with regards to that relation only. More recently, Khadangi et al. [60] addressed a similar sampling context taking Facebook as case in point, by proposing a biased sampling techinque for a multilayer activity network, where the activities are regarded as multiple social interactions (e.g., like, comment, post and share). The idea is to use a reinforcement learning scheme, i.e., learning automata [112], in order to learn transition probabilities among the users, and then apply a random walk-based sampling on the activity network using the learnt probabilities. The proposed



Figure 8: The "lunch" and "Facebook" layers in the AUCS networks sampled according to (a) random node choice and (b) snowball sampling.

approach allows to perform a biased sampling, i.e., obtain a sample subgraph consisting of suitable nodes according to application-based measures, such as fame, spam, politeness, trust, closeness, and time spent on the social network.

Examples of random and snow-ball sampling simplification are shown in Figure 8. Notice that while the principles are the same as in simple networks, sampling in multilayer networks require additional details. For example, in Figure 8(b) when an actor that is present on another layer is encountered, its neighbors in the other layer are also retrieved.

3.2. Aggregation based techniques

Aggregation refers to techniques that aim to obtain a more compact version of the input multilayer graph by employing partitional or hierarchical grouping mechanisms that involve the building blocks of a multilayer graph (i.e., nodes, edges, layers). Note this differs from selection techniques, which rely on the selection of a subset of nodes, edges, or layers and evaluate them individually.

We organize our presentation of aggregation techniques into five categories, namely *flattening*, *community detection*, *coarsening*, *positional equivalence*, and *graph compression and summarization*. Flattening methods transform the input multilayer network in a single-layer (weighted) network by discarding the information that characterizes the individual layers of the network, thus aggregating them into a single layer. Multilayer community detection methods allow the definition of simplification functions to map actors/nodes to cohesive groups. Positional equivalence methods leverage the notions of structural equivalence and interchangeability to obtain a simplified network. Graph compression and summarization approaches, which are originally conceived to deal with large graphs, aim to reduce the size of the graph and improve the efficiency in terms of storage and execution time. Similarly to graph compression and summarization, coarsening or graph contraction aims to enable the application of computationally expensive algorithms on large graphs by building a hierarchy of successively aggregated graphs with decreasing size. In the following, we will discuss in detail each of the above categories of aggregation based techniques.

3.2.1. Flattening

When dealing with multilayer networks, handling and analyzing the network can be problematic when the number of collected layers is relatively high. Moreover, applicability of standard network analysis techniques is not guaranteed on multilayer models. A straightforward solution in these cases is to *flatten* the network, i.e., given a multilayer network $G = (\mathcal{A}, \mathcal{L}, V, E)$, discard the information about the layers \mathcal{L} . The result of a flattening process is a single-layer network, where the edge set contains a single instance of each relation between two nodes, i.e., all the information about edge types (e.g., different types of relations happening or not between a pair of nodes) will be lost. As defined in [28], a basic (unweighted) flattening of a multilayer network $G = (\mathcal{A}, \mathcal{L}, V, E)$ is a graph (V_f, E_f) where $V_f = \{a | (a, l) \in V\}$ and $E_f = \{(a_i, a_j) | \{(a_i, l_q), (a_j, l_r)\} \in E\}$.

In order to avoid a complete loss of information about edge types, basic flattening can be improved by including edge weights proportional to the number of edges between two actors in the original network, i.e., the number of layers where a certain edge existed in the original network. A more sophisticated way to flatten a multilayer network can be based on the use of a weighting scheme which assigns a weight $w_{q,r}$ to each pair of layers (l_q, l_r) , so that the resulting single-layer network can be expressed as a linear combination of the original multilayer network. As defined in [28], for a multilayer network $G = (\mathcal{A}, \mathcal{L}, V, E)$, given a $|\mathcal{L}| \times |\mathcal{L}|$ matrix whose generic entry $w_{q,r}$ indicates the weight to be assigned to edges from layer l_q to layer l_r , a weighted flattening of G is a weighted graph (V_f, E_f, ω) where (V_f, E_f) is a basic flattening of G and $\omega(a_i, a_j) = \sum_{\{(a_i, l_q), (a_j, l_r)\} \in E\}} w_{q,r}$. An alternative to complete flattening is proposed by De Domenico et al. [25],

An alternative to complete flattening is proposed by De Domenico et al. [25], by means of a layer aggregation technique which aims at finding a compromise between the original multilayer network and a complete flattening. The idea is to aggregate most *similar* layers, based on the assumption that some layers may contain redundant information, i.e., they may show a similar topology. The proposed technique is based on an agglomerative hierarchical clustering schema, where the leaves of the dendrogram are the original layers, and the root is the flattened graph (and intermediate levels represent consecutive layer aggregations). Jensen-Shannon divergence is used to measure distance between layers, while the quality of each aggregation is evaluated based on information loss, measured using Von Neumann entropy. The best solution is chosen as the one corresponding to the level of the dendrogram containing the aggregation minimizing the information loss, thus providing an aggregated multilayer network representing the best trade-off between the extent of the simplification (i.e., number of aggregated layers) and information loss.



Figure 9: A dendrogram showing how similar different layers are in the full AUCS network. This type of information can be used to decide which layers to merge, and this dendrogram has been computed using the inverse Jaccard coefficient to measure the portion of edges present in both layers, for each pair of layers.

Since the main objective of flattening is that to allow the applicability of single-layer techniques on multilayer networks, in most cases task-based flattening approaches have been proposed in relation to specific network analysis tasks, e.g., community detection [9].

The choice of which layers to merge (in this case, flatten) is often based on domain knowledge. Figure 9 shows how some implicit information about the similarity between different layers is however already present in the data: several layer comparison measures are presented and compared in [13].

3.2.2. Multilayer community detection

Discovering an organization of the network into densely-connected subgraphs, i.e., clusters or communities, naturally achieves a common way of simplifying a graph in terms of mesoscopic structural features due to group properties. Clearly, as a consequence of the learned community structure, the resulting communities could also be used to select subgraph(s) from the original network in order to support focused tasks.

In recent years, the problem of identifying communities has gained attention and several community detection methods specifically conceived for multilayer networks have been developed in the last few years [62, 77, 64]. Community detection methods for multilayer networks can be broadly grouped into three categories, namely: flattening-based [28, 9], layer-by-layer [10, 129, 130], and direct (or multilayer) [24, 67, 2]. The first group of methods are commonly used to flatten a multilayer network to enable the use of abundantly available singlelayer community detection methods. The second category consists in processing each layer of the multilayer/multiplex network separately, and then aggregating the results. The last class of methods operates directly on the multilayer network model.

Layer-by-layer can be divided into three branches: pattern mining [10], matrix composition, and consensus matrix. Pattern mining detects communities in each layer separately using a simple-graph community detection, then makes use of pattern mining algorithms to aggregate the resulting communities. Matrixcomposition-based methods [129, 130] extract structural features from each dimension of the network via modularity analysis, and then integrate them all to find out a robust community structure among actors. The latter group of methods, consensus-matrix-based methods, combine multiple solutions over the various layers to infer a single community structure that is representative of the set of layer-specific community structures.

The multilayer group of methods includes clique-based methods [2], which exploit the concept of multilayer cliques to identify multiplex communities, random walk-based methods [24, 67], which introduce a multilayer random walker that can traverse inter-layer edges, modularity-based methods [92, 19], which define a multilayer modularity function and optimize it to produce the community structure solution, label propagation methods, which utilize a multilayer affinity measure among actors given their connections on different layers and then introduce a labeling method for the actors controlled by these affinity scores, and within-group connectivity local methods, which define a multilayer within-group connectivity function for the multiplex community and tries to maximize that function.

In addition to the above categorization, we can identify an extra group of methods under the node-centric (or local) name. These query-dependent methods are designed to discover local communities starting from a group of seed nodes, and result particularly useful when global information on the whole network are missing.

Figure 10 shows the communities identified by the generalized Louvain method in the AUCS network. In this case, each node belongs to exactly one community, that is, the communities define a partitioning of the node set. One can thus easily created a new network with only five nodes on each layer, to study the relationships between communities instead of the relationships between individual actors.

3.2.3. Coarsening

The concept of graph coarsening (sometimes referred to as contraction [40, 4]) refers to a family of simplification approaches aimed at building a hierarchy of successively coarsened (i.e., aggregated) graphs with decreasing size [16]. The general idea is to enable the application of computationally expensive algorithms by running them on the coarsened graph, then obtaining a solution for the original graph through an uncoarsening (i.e., expansion) phase.

For simple graphs, a basic coarsening approach consists in contracting two nodes (i.e., a single edge) at each level of the hierarchy. Though being extremely simple, this method tends to result in a hierarchy with as many levels as the



Figure 10: Communities in the AUCS network. Each community can be replaced by a single node in each layer, with weighted edges between the new nodes to indicate how many edges (or which percentage of edges) were originally present between nodes from the two corresponding communities

nodes in the original graph, and for this reason is referred to as n-level approach [99]. Another well know coarsening strategy is based on the contraction of matchings (i.e., pair of nodes connected by edges non-incident to each other), which leads to a logarithmic number of levels. As a general rule, a good matching should contain high weighted edges, and relatively uniform node weights. This trade-off can be handled using an *edge rating* function [54, 117, 116], and specific solutions have also been proposed for scale-free complex networks [43].

The typical application of coarsening is in graph partitioning, where the combination of coarsening and partitioning techniques is referred to as *Multilevel Partitioning* [15, 51, 59, 68], where the idea is to exploit the multilevel hierarchy of contracted graphs produced during the coarsening phase in order to efficiently obtain an initial partitioning, which is then refined during the uncoarsening phase in order to obtain a solution for the original graph. Coarsening-based multilevel partitioning methods are often used to address graph drawing problems. In fact, classic force-directed graph drawing algorithms [38], when dealing with large graphs, can easily get stuck in a local minimum. Using a multilevel approach allows to find global optimal layouts for (relatively small) graphs in the lower levels of the hierarchy in reasonable time, which are then used to build a solution for the original graph through an iterative refinement process. Several graph drawing algorithms based on this multilevel approach have been proposed, which are able to produce high-quality drawings for large graphs, i.e., scalable up to millions of nodes [134, 47, 55, 83].

To best of our knowledge, no specific coarsening techniques have been proposed for multilayer network models. An intuitive reason can be that contracting adjacent nodes and edges can be naturally thought as a *layer-wise* action, so that taking into account different layers at the same time may be redundant or misleading. In other cases (i.e., where the source of complexity lies on the number of layers) layer aggregation approaches may be preferred in order to solve similar problems (cf. Section 3.2.1). Nevertheless, we believe that native multilayer coarsening approaches can be envisaged based on the contraction of inter-layer edges and/or exploiting multilayer information about a node's neighborhood (e.g., leveraging on relevance-based measures [11]). Such techniques may also help to advance research on multilayer network visualization, which is still a challenging problem [26].

3.2.4. Positional equivalence

Another common approach to analyze social networks is to study their *struc*tural roles and *structural positions*. That is, finding actors, or groups of actors, whose local connectivity in the graph define their role in the social network. This idea, known as positional equivalence, was originally developed by the sociologists Lorrain and White in the early 70s [78], under the assumption that actors related to exactly the same other actors in the network must share an equivalent social behaviour.

The main difference between both structural entities, positions and roles, has been largely discussed in the literature. The definition provided by Wasserman and Faust [138] ³ emphasizes that *structural roles* refer to actors with similar patterns of connectivity, independently of the specific actors to whom they are connected (e.g., hubs in a network); while *structural positions* are based on the concept of interchangeability: two actors in the same structural position can be swapped without changing their relationships with other actors in the network.

The most straightforward and strict type of equivalence is *structural equivalence* [36], which places nodes in the same position if, and only if, they have the same connections (i.e., the set of adjacent nodes is identical). This type of equivalence is difficult to find in practice in large and/or complex networks and can be replaced by *regular* [79], *automorphic* [34] and *stochastic* [53] definitions of equivalence, which are able to find more flexible types of positions. In short, the stochastic equivalence definitions assign nodes of the graph to the same role if they have the same probability distribution of edges with other nodes.

The most common and extended methods to detect roles in social networks are *block-modeling* [115] methods, which allow the representation of a network using an image matrix where the nodes, grouped into blocks, represent structurally equivalent roles or stochastically equivalent positions, and the edges represent interactions between them. In the past years, new block-modeling methods has been developed to find roles in complex graphs such as two-mode [33] and multilevel [142] networks. One of the main applications of stochastic blockmodels and similar generative methods is to detect network communities, as the image matrix represents — under certain conditions — a partition of the network that maximizes the posterior modularity coefficient of the partition [106, 107]. Many advancements in the field have been limited to finding community struc-

 $^{^{3}{\}rm The\ terms\ } role-equivalent$ and role-similar are also commonly used to refer to the original notions of role and position

tures restricted to particular layers [126] or pillars [105]. In a recent paper, Pamfil et al. [101] proposed a block-modeling method to detect different types of structural roles and positions for various types of multilayer structure, including temporal, multiplex, and multilevel (i.e., hierarchical) networks.

While block-models are the most popular methods to find positional equivalences, there are also other methods to compute structurally equivalent or similar roles based on similarity measures (e.g., Euclidean distances, correlations) computed on the structure of the nodes of the graph and/or their attributes [50]. However, to the best of our knowledge, in multilayer networks these methods have been only used in combination with some of the aforementioned blockmodeling methods [107].

3.2.5. Graph compression and summarization

Graph compression and summarization refer to a set of simplification techniques created in order to improve the volume and storage of the network, usually with the goal of speeding-up graph algorithms, queries [35] or the visualization of large graphs [81, 76]. While both concepts have been used interchangeably, they differ on their main objective. In general, summarization or *semantic graph compression* techniques focus on compressing structural features of the graph that have a semantic in a specific application domain, usually for visualization purposes. The goal of these methods, therefore, is not very different from the goal of the sampling and coarsening methods we have introduced above, and hence we will not review them here.

Algorithmic graph compression aims instead to loosely reduce the graph size for an efficient execution of graph mining tasks [35, 133, 74, 61, 97]. The perfect graph recovery is sometimes unfeasible, therefore most of the recent advancements in graph compression have focused on developing faster algorithms that guarantee an acceptable recovery rate [82].

Most of the algorithms for graph compression are based on the ideas from Navlakha et al. [93], who proposed using a two-part Minimum Description Length (MDL) [113] codification to represent the simplified network. The idea is to represent the original graph $G = (V_G, E_G)$ using two components: an aggregated or coarsened graph $S = (V_S, E_S)$ and a set of corrections C. The summary S is a simplified network with considerably fewer nodes and edges that can easily fit in memory, while the corrections are two sets representing the edges that should be added or removed to S in order to recover the original graph. The size of C depends on the specific structure of the original graph Gand on the level of compression applied. Figure 11 shows an example where the original 8-node graph is compressed into a summary of 4 super nodes.

Several proposals appeared recently to deal with attributed nodes and edges, allowing to compress weighted [61, 133] and temporal networks [122]. However, a difficult research question left unanswered in the literature is how to adapt graph-compression techniques to complex graph structures, such as multilayer networks [76]. While most of the coarsening and sampling methods for multilayer networks described in Section 3.2.3 and Section 3.1.2 could potentially be used to generate a summary of the graph, researchers have not found yet



Figure 11: The two-part MDL representation proposed in [93]: original graph (G), graph summary (S), corrections (C), and the super-node mappings.

a correction algorithm or structure able to simultaneously recover the original network while reducing the representation size of the graph in memory.

Methods based on node grouping, for example, can efficiently reduce the size of the intra-layer graphs, but this will not reduce the amount of storage as we still need to keep track of the inter-layer edges within the original nodes across several layers. On the other hand, while structurally equivalent positions can be seen as graph summaries with no errors, they are extremely rare in real networks, which makes them unsuitable for graph compression.

3.3. Transformation

All simplification methods result in the removal of some objects, e.g., edges or nodes, from the network. In the previous two sections we have discussed approaches that just remove some objects, without replacing them with anything else (selection) and other approaches replacing the removed objects with less objects of the same type, e.g., replacing groups of nodes with a single one (aggregation). The final main class of simplification methods shares with the previous two the fact that some objects are removed from the network, but in this case the removed objects are replaced by (that is, transformed into) objects of a different type.

3.3.1. Projection-based

The term *network projection* generally refers to simplification techniques dealing with two (or more) node types in a network. The traditional approach consists in reducing the number of node types by replacing edges between two node types with edges between the same types of nodes, and removing one of the node types.

For instance, given a two-mode network with node types A and B, the typical projection approach consists in removing type-B nodes and adding an



Figure 12: (a) Author and paper layers in the AUCS network. (b) A projection of the papers on the author layer.

edge between any pair of type-A nodes originally connected to the same type-B node [120]. As a practical example, a two-mode co-authoring network containing *author* and *publication* nodes can be simplified by inserting an edge between two author nodes when they are both connected to at least a common publication node, thus discarding the *publication* type.

Even if we do not explicitly take into account networks including heterogeneous node types in this work, in a multilayer context it is easy to think about the same process for nodes belonging to different layers, i.e., nodes belonging to two different layers l_a and l_b can be thought of as nodes of two different types A and B (i.e., the *author* and *publication* node types in the previous example can be easily modeled as two different layers in a multilayer network).

Nevertheless, the standard projection approach described in the previous example shows several shortcomings. First of all, all the information regarding multiple connections between the same pair of nodes would be lost, e.g., number of common publications between two authors. Moreover, it tends to generate large cliques, especially in presence of extremely popular *hub* nodes of the type being discarded. Padrón et al. [100] introduced a weighted projection technique which tries to overcome these limits by weighting the edges with the number of common connections from which they are originated. More advanced weighting schemes are proposed in [94, 98], e.g., based on the concept of network relevance and with weights redistributed according to the exclusivity of the collaborations.

Figure 12 shows how a projection can be used to create a simple network (or a simple layer) starting from two layers with different node types and inter-layer edges.

3.3.2. Graph-embedding-based

Graph embedding techniques aim to transform a graph in a low-dimensional representation, enabling the use of a rich set of tools mostly based on stateof-the-art machine-learning methods [17]. A clear advantage in obtaining a low-dimensional representation is to reduce the memory-footprint requirements while retaining relevant information for the task at hand [8]. Example tasks include node classification, node clustering, node recommendation, retrieval and ranking, link (i.e., edge) prediction, and graph classification [44]. Moreover, since the embedding corresponds to a vectorial representation, vector operations on the learned model might in principle be computationally more convenient than graph operations. Another task which benefits from graph embedding techniques is network visualization. Given the rising complexity and volume of current networks, graph embedding techniques represent an essential tool to reduce the size of the network, capture meaningful patterns and thus build visual representations which can easily convey properties and structural information of complex networks. Traditional visualization algorithms seek to find a compromise between clarity of structural characteristics and aesthetic requirements such as fixed edge lengths or minimal edge crossing (e.g., [58, 102, 31]) while resorting to *multidimensional scaling* to find a low-dimensional representation of high dimensional data, with the goal of preserving pairwise dissimilarities in terms of Euclidean distance [12, 3].

The general goal of a graph embedding process is to learn a function f that maps one or many features of the network (i.e., nodes, edges, or the whole graph) to a new *d*-dimensional space \mathbb{R}^d . For instance, in the case of node embedding for a multilayer network, the function to learn can be of the form $f: \mathcal{A} \to \mathbb{R}^d$ or $f: V \to \mathbb{R}^d$. In effect, graph embedding approaches can be classified based on the constituent(s) of a graph they are designed for. Several works have been recently developed for nodes [109, 45], edges [141], subgraphs (e.g., communities [137, 21]), and whole-graph embedding [90, 96, 91].

Matrix factorization based algorithms [52, 49, 139] are the pioneering methods in graph embedding, since they apply a decomposition technique to a matrix representation of an input graph. There are mainly two types of matrixfactorization-based graph embedding: factorization of graph Laplacian eigenmaps, and direct factorization of the node proximity matrix [17]. One of the earliest methods designed for multilayer networks, specifically for community detection purposes, is Principled Modularity Maximization (PMM) [129]. PMM infers a latent community structure for the nodes in a multilayer network by performing a two-step methodology. Firstly, PMM extracts low dimensional vectors from each layer through modularity maximization and aggregates the extracted information through cross-dimension integration. Finally, a simple kmeans is carried out on the learned representation to find out the communities of the network.

From a different perspective, in the LINE method [128], two functions are defined for both first- and second-order proximities, where first-order proximity refers to edge weights and second-order proximity refers to neighborhood similarity. LINE defines two joint probability distributions for each pair of nodes and minimizes the Kullback–Leibler (KL) divergence of these two distributions.

More recently, there has been momentum for the development of *deep-learning-oriented* techniques. DeepWalk [109] and Node2Vec [45] are two exemplary random-walk-based methods. According to the *Skip-gram* [86] model, these methods treat nodes as words and paths as sentences, then apply deep learning to the sampled random-walk paths. As the skip-gram model aims to maximize the co-occurrence probability among the words that appear within a window in the same sentence, the resulting graph embedding by DeepWalk and Node2Vec preserves first- and second-order proximity of nodes.

Other deep-learning-oriented methods include the use of autoencoders and their variants (i.e., denoising, variational, etc.), which aim to maximize the reconstruction accuracy of the input graph, by applying a *decoder* block to the latent representation learned by an *encoder* [132, 18, 135]. Another deeplearning common approach is to directly apply a convolutional neural network (CNN) to Euclidean data generated from a graph [96], or to adapt CNN to graphs [63, 118]. In addition to this group of methods, GraphSAGE [48] aims to learn a function that generates embeddings by sampling and aggregating features from a node's local neighborhood. GraphSAGE, which can be seen as an extension of the GCN [63] framework to the inductive setting, can deal with evolving graphs and it can easily generate embedding vectors for previously unseen nodes.

Graph embedding for multilayer networks. At the time of writing of this paper, there is a relatively small corpus of methods of graph embedding specifically conceived for multilayer networks, namely: PMNE [75], MNE [140], and MELL [85].

The first two methods adapt and extend the Word2Vec [87, 88] model to multilayer and multiplex networks, respectively. The input sentences (i.e., paths) are generated by a second-order random walk process, which is constrained to explore one layer at the time, with the exception of PMNE Layer co-analysis method in which the random walker gains the ability to jump from a layer to another. As depicted in Fig.13, PMNE includes three different approaches: two naive baselines, and one natively multilayer. In the Network Aggregation approach, the multilayer network is merged into a single weighted network (where multiple edges between two nodes are not allowed) and the embeddings for actors are computed on the aggregated network, i.e., $f : \mathcal{A} \to \mathbb{R}^d$. In the Results Aggregation approach, the embeddings are computed separately on each layer and then successively concatenated together, i.e., $f_l: V \to \mathbb{R}^{d_l}$ and $f = f_1 ||f_2|| \cdots ||f_{|L|}$ with $f: V \to \mathbb{R}^{d'|L|}$. Unlike the previous two approaches, in the Layer Co-analysis approach the second-order random walker acquires the ability to jump across layers, allowing the generation of walks that are not limited to a single layer of the network, i.e., $f: V \to \mathbb{R}^d$. In all of the three approaches, the Node2Vec model is chosen to be applied on the generated paths.

MNE generates a layer-wise embedding \mathbf{v}_n^i , for every node *n* and layer *i*, which consists of an embedding \mathbf{b}_n shared across all the layers and that describes



Figure 13: Architecture of PMNE: (a) Network Aggregation, (b) Results Aggregation, (c) Layer Co-analysis [75].

the node *n* globally, and a local (i.e., layer-wise) embedding \mathbf{u}_n^i :

$$\mathbf{v}_n^i = \mathbf{b}_n + w^i \cdot \mathbf{X}^{i^T} \mathbf{u}_n^i$$

In the above equation, w^i denotes the importance of layer *i*, and \mathbf{X}^{i^T} is a transformation matrix that aligns the global and local embedding vectors.

MELL is based on a regression framework, and unlike the previously described methods, it also takes into account the directionality of the edges (i.e., $(u, v) \neq (v, u)$) by using two vectors for each node \mathbf{v}_H and \mathbf{v}_T . Node embeddings belonging to the same node are enforced to be close to each others through a regularization term. In addition to node embedding, MELL also learns a set of *layer vectors* representing layers' connectivity, in order to differentiate edge probabilities in each layer. The probability between two nodes v_i^l and v_j^l , both belonging to the layer l, is equal to:

$$q(\mathbf{v}_i^l, \mathbf{v}_j^l) = \frac{1}{1 + \exp\left(-(\mathbf{v}_i^l + \mathbf{r}_l)^T \cdot \mathbf{v}_j^l\right)}$$

where \mathbf{v}_i^l (resp. \mathbf{v}_j^l) denotes the embedding vector for v_i^l (resp. v_j^l), and \mathbf{r}_l is the vector embedding for the *l*-th layer.

Both MELL and MNE are well-suited to link prediction and node classification, where high-order proximity information, extracted through random walk, turns out to be particularly expressive. MELL could be preferred when the information carried by edge directionality is essential for the task at hand. Conversely, MNE might in principle be more suited to exploit both global and local node-embeddings.

4. Discussion

Building upon our analysis in the previous sections, here we provide a few remarks that are concerned with the following two questions: **(RQ1)** What are the main characteristics that would make a given approach appropriate or not for a given simplification task? and, **(RQ2)** How is research on network simplification going to evolve, given the existing corpus of simplification methods?

Concerning **RQ1**, we will focus on practical usability criteria to determine whether a simplification approach is appropriate or not for a problem at hand, namely the parts of the network that are affected, whether the result is deterministic, and whether the simplification process is reversible (cf. Table 2). It should also be noted that the variety of network simplification tasks and, consequently, the diversity in their respective analysis purposes makes it difficult to devise a unified framework for the evaluation of network simplification methods. Ultimately, this could be useful to support the choice of a specific algorithmic solution among different alternatives. For simple graphs, we can recognize a number of evaluation aspects that might be meaningful and relevant for any of the network simplification approaches; these aspects certainly include the opportunity of measuring, from one or more perspectives (i.e., micro-, meso- and macroscopic), the extent to which the simplified network preserves selected structural properties in the original network and whether other structural properties are changed. Estimating the sampling bias is clearly a crucial aspect for methods in the selection-oriented simplification category, while aspects relating to information loss may also be of interest to evaluate the quality of transformation- and aggregation-oriented methods. Compression ratio and related concepts, with their impact on the spatial complexity, might represent useful indicators for memory-footprint requirements of the simplification method.

Practical usability is also related to the availability of software implementations. According to our findings, several simplification methods for multilayer networks are still to be invented. Therefore, software support for multilayer networks in general, and simplification approaches in particular, is still more limited than what is available for non-multilayer networks. However, some of the methods reviewed in this article come with freely available software implementations, and some are also available as part of multilayer network analysis libraries, either as single function calls or requiring some limited coding. In Section 4.2, we review these implementations.

4.1. Practical usability aspects

4.1.1. Key-enabling and Affected elements

Even though multilayer networks are defined over a richer set of elements, it can be noted from Table 2 that most selection- and aggregation-oriented methods rely on (and affect) basic network elements, i.e., nodes (set V) and edges (set E). Moreover, all methods aim at reducing the number of nodes and edges in the network. This is not surprising, since most techniques represent adaptations to multilayer models of methods which were designed for single-layer networks. As a matter of fact, the main exceptions in this scenario are represented by the families of methods that are specifically tailored to multilayer networks, i.e., flattening and layer aggregation. A different relation between key-enabling and affected elements can be observed for transformation-oriented methods. Concerning projection, this is the only case where increase in an affected element (E) can be observed. A slightly different situation occurs for embedding-based methods, where a new edge set is derived from a certain embedding space (over nodes or actors), which is forced to be smaller in size with respect to the original one. Summarizing, while selection- and aggregationoriented methods always aim at a simplification which results in a reduction in size of the original network, transformation-oriented methods rely on a different concept of simplification (i.e., suppressing a node type for projection, and obtain a low-dimensional representation of the network in the case of networkembedding).

4.1.2. Determinism

Looking at the fifth column of Table 2, it can be noted that selectionoriented simplification methods can be non-deterministic, especially in sampling approaches. These inherently rely on non-deterministic techniques that aim to produce a subnetwork (sample) exhibiting similar properties as compared to the original network, whereby nodes or edges are randomly picked to start the building of the sample. Also, in model-based filtering, non-determinism may arise due to the sampling of ensembles of networks according to constraints on degree, strength and other properties based on probabilistic generative models.

Aggregation-oriented simplification mostly includes deterministic methods, provided that no randomization or low-rank approximation techniques are used, as it might be the case for coarsening and multilevel-partitioning (where the hierarchical approximation obtained via coarsening is sequentially refined over all levels of the hierarchy until it accomplishes the task for the original input with some approximation for it), and for some community-detection methods such as, e.g., label propagation, whose uniqueness of solutions is not ensured.

Transformation-oriented simplification techniques are deterministic when dealing with network projection tasks, whereas embedding-based transformation should be regarded as non-deterministic when low-rank approximation techniques are used to compute the embeddings.

4.1.3. Reversibility

Concerning reversibility, a general remark is that simplification methods are usually designed without any particular requirement in terms of ability to reconstruct the original network from a simplified one, and hence simplification is typically interpreted as irreversible. For instance, this is the case of multilayer community detection, whereby a task of aggregation-oriented simplification would in principle be carried out over the output community structure without storing the full topology of the original network.

Methods whose outputs could be reversed include multilevel partitioning, positional equivalence, graph compression, and coarsening, as long as the existing methods are natively equipped with procedures that enable reversibility or recovery of the simplification process; however, none of such reversible approaches has a multilayer counterpart.

This would raise the opportunity for developing reversible methods, in particular for compression and coarsening, that are specifically conceived for multilayer networks. In particular, it would be interesting to investigate the minimal requirements in terms of network information that needs to be indexed and stored, in order to reconstruct the original graph, or infer it with a bounded approximation guarantee, in relation with existing simplification techniques.

4.1.4. Single-layer vs. Multilayer native methods

We have noticed that most simplification techniques correspond to adaptations or extensions to multilayer networks of methods natively designed for single-layer networks. However, the picture is quite variegate and contains exceptions. As reported in Table 2, some of the simplification methods are only available for single-layer networks, which is the case of graph compression and coarsening, or no counterpart has been yet developed for multilayer networks, as for multilevel partitioning. By contrast, other methods are conceived for multilayer networks only, such as node-layer relevance filtering, flattening, and layer aggregation. Moreover, when there is wide corpus of studies available for certain categories, i.e., centrality-based filtering, our focus was directly on the existing methods that can simplify multilayer networks.

	1 able 5: Available implementa	TIONS OF N	алуе терподз юг типлауег пермогк sumplification.
category	method	Refs.	Public repository
	centrality-based filtering	[123] [39]	https://github.com/manlius/muxViz https://github.com/egalimberti/multilayer_core_decomposition
Selection	node-layer relevance filtering	[114]	https://bitbucket.org/uuinfolab/uunet
	model-based filtering	[80]	http://people.dimes.unical.it/andreatagarelli/emcd/
	sampling	I	
		[24]	https://github.com/manlius/muxViz
	community-detection-based	[2]	https://bitbucket.org/uuinfolab/uunet
		[56]	http://people.dimes.unical.it/andreatagarelli/mllcd/
	multilevel partitioning	×	
Aggregation	positional equivalence	[142]	https://cran.r-project.org/web/packages/blockmodeling/index.html
	flattening	Ţ	
	layer aggregation	[25]	https://github.com/manlius/muxViz
	graph compression	×	
	coarsening	×	
	projection-based	I	
Transformation	embedding-based	[75] [140]	https://github.com/tangjianpku/LINE https://github.com/HKUST-KnowComp/MNE

Ę.
岩
~
0
- E
р.
d
- H
·
S S
<u>-</u>
8
0
8
5
5
a
-
- 5-1
- di l
5
~ ~ .'
<u> </u>
·:::!
±.
- EI
=
в
-
- HI
0
ч
121
S
0
a
5
×.
8
_
Ð
5
-i
+
at
nat
nat
of nat
of nat
s of nat
ns of nat
ons of nat
ons of nat
tions of nat
ations of nat
tations of nat
ntations of nat
entations of nat
entations of nat
nentations of nat
ementations of nat
lementations of nat
olementations of nat
plementations of nat
nplementations of nat
implementations of nat
implementations of nat
e implementations of nat
ole implementations of nat
ble implementations of nat
able implementations of nat
ilable implementations of nat
ailable implementations of nat
vailable implementations of nat
vailable implementations of nat
Available implementations of nat
Available implementations of nat
: Available implementations of nat
3: Available implementations of nat
3: Available implementations of nat
e 3: Available implementations of nat
ole 3: Available implementations of nat
ble 3: Available implementations of nat
'able 3: Available implementations of nat
Table 3: Available implementations of nat

4.2. Multilayer network simplification software

Table 3 records all the openly available implementations of the native multilayer methods and algorithms discussed in this review, accessed on January, 2020. Some of the aggregation methods, such as multilevel partitioning, graph compression and coarsening do not have any openly available implementation because we do not have any reference algorithm (See Table 2). We have indicated them in Table 3 with a \times symbol. For others methods, such as sampling, flattening and projection-based transformations we have one or more reference works describing a native multilayer method, but the authors have not included any reference or link to an openly available implementation. In summary, we have found that only 11 of the simplification methods in this review categorized as native multilayer contain a reference to some public available implementation or repository.

Formally, multilayer networks are graphs where nodes are complex objects made of actors and layers. Therefore, in some cases the authors have used libraries for simple graphs to perform some operations on multilayer networks and implement some of the methods described in this article. However, none of the papers using this methodology provide a link to an open-source repository.

General libraries. Some specific libraries are available providing native multilayer network objects and manipulation functions. In this section we focus on these libraries, and in particular multinet,⁴ muxviz,⁵ and pymnet.⁶

Selection methods are not directly available as single software functions, but some of them can be implemented using other functionalities provided by the reviewed libraries. The multinet library provides a selection of centrality measures and relevance functions in addition to functions to remove nodes and edges, and their combination can easily be used to perform centrality-based and node-layer relevance filtering. The pymnet library provides a function to produce induced subgraphs that can be used together with its functions to compute centrality measures and clustering coefficient. The muxviz library also provides the computation of some centrality measures, although the library is more oriented towards visual analysis than network manipulation. Model-based filtering and sampling are not currently supported, although simple sampling based on uniform probability or probabilities computed from centrality values can easily be implemented using multinet and pymnet writing some additional R, C++ (for multinet) or Python code.

Support for aggregation is limited. Both multinet and muxviz provide a selection of community detection methods, but they do not provide a direct

 $^{^{4}\}rm https://CRAN.R-project.org/package=multinet, last update on git repository: January 2020, main usage with R, C++ code also available$

 $^{^5\}mathrm{http://muxviz.net,}$ last update on git repository: January 2018, main usage through a visual interface

 $^{^{6}\}rm https://bitbucket.org/bolozna/multilayer-networks-library, last update on git repository: July 2018, main usage with python$

way to aggregate communities into single nodes. A flattening function is implemented in multinet, both for weighted and unweighted multilayer networks. A method to aggregate layers, also mentioned in this survey, is available on muxviz, whereas pymnet provides an aggregation function to reduce the number of aspects. Multilevel partitioning, positional analysis, graph compression and coarsening are not supported.

Concerning transformation methods, a previous version of **multinet** provided a projection function, not present in the current version. None of these libraries include embedding methods, which cannot easily be implemented just using the available functions because they require machine/deep learning engines.

In summary, support for simplification methods is still very limited, although some of the approaches are available. Looking at some general libraries for multilayer network analysis, our general perception is that some of the approaches described in this article would require very little effort to be integrated in existing software, being based on basic functionality that is already available. Others, such as the approaches based on positional analysis, would require some additional effort to implement new algorithms from scratch. Methods such as network embedding may require the integration with other software providing the machine/deep learning algorithms required by these approaches. The taxonomy we introduced in this article can be used as a roadmap to guide the integration and development of simplification methods in existing libraries.

5. Research Directions

In relation to **RQ2** stated in the previous section, here we focus on the future evolution of multilayer network simplification, which is still in its infancy. We shall identify underrepresented categories of simplification methods for multilayer networks. We will highlight the most evident limitations of the existing methods, for each of the categories, and raise the emergence of novel classes of methods for enhancing network simplification tasks.

5.1. Coverage and limitations of existing approaches

Selection-oriented simplification methods are relatively well-represented in the multilayer context, since for each of the approaches belonging to this category, there is at least one equivalent method conceived for multilayer networks. In the last two decades, we have witnessed the development of a plethora of centrality measures, mostly designed for single-layer networks. Recently, a relatively large corpus of study has addressed the extension and adaptation of single-layer centrality measures to multilayer networks (cf. Section 3.1.1). Nevertheless, it appears that the potential of multilayer centrality methods might still be unveiled. Two promising alternative approaches to the simplification process are based on node-layer relevance and model-based filtering; however, the design of such methods for multilayer networks is still in its infancy. Moreover, as concerns sampling approaches, the only methods for multilayer networks (i.e., [42] and [60]) belong to the exploration-based sampling subcategory, whereas no representative exists for the random access subcategory.

Aggregation-oriented simplification category includes methods characterized by relative numerosity of methods such as multilayer community detection and, to a lesser extent, position equivalence, but also by types of methods that are underrepresented or not represented at all. For instance, multilayer aggregation counts only the method proposed in [25] by De Domenico et al., flattening enumerates two methods [28, 9], whereas no multilayer extensions have been so far proposed for graph compression and coarsening.

As concerns transformation-based techniques, on the one hand, projectionbased methods can be borrowed from multi-mode network context, since it is straightforward to compare different node types to nodes belonging to different layers. On the other hand, the graph embedding vein experienced an unceasing and growing attention in the last few years. Nonetheless, only a handful of methods have been specifically devised for multilayer networks. The process of designing a graph embedding method includes several sensitive components which individually could decree the success or failure. One of the most challenging tasks lies in the way we gather structural information from the graph, e.g., by exploiting random walks, or whether we chose to use a more compact representation such as the normalized adjacency matrix. Another critical step which directly affects the amount of information retained into the learned representation is the encoding function the model aims to learn, which is in charge of leveraging the input data by encoding it in every node-embedding. Another essential component is represented by the loss function which drives the learning process, and iteration by iteration determines the final quality of the learned representation. Assuming to be able to successfully design the above-stated components of a model, the elephant in the room is represented by scalability and the need for re-training the model in the case where even a single node is added to the graph (this issue in particular affects most of the methods for both multilayer and single-layer networks currently in the literature).

5.2. Future directions

The increasing ability of gathering and storing huge amounts of data and, consequently, the opportunity of modeling rich-content networks in several domains, raises the need for the development of next-generation simplification methods, which should be effective in leveraging external knowledge or sideinformation as well as time-based attributes when dealing with the complexity of multilayer networks.

Simplification for attributed networks. Accounting for rich-content information that may be associated with actors, nodes, edges and/or layers represents an interesting direction to enhance the quality of a network simplification task. However, when available, such information is often sparse and incomplete, therefore one challenge is to develop methods that can profitably exploit such information and properly embed it within the structure space, which becomes further complicated in a multilayer network setting. Simplification for time-evolving networks. Most existing methods of multilayer network simplification deal with static graphs, focusing on single snapshots of the complex system while discarding the time dimension across the layers. Therefore, effort should be made toward the development of simplification methods that are able to fully leverage the temporal dimension and the evolution of a multilayer network over time, which might be beneficial for evolutionary as well as online/stream processing tasks.

Improving interpretation of multilayer network representation feature. We discussed the role of deep neural networks in representation learning problems to support transformation-oriented simplification. As in other data domains, however, deep-learning-based techniques generally fail in providing learned representations that are highly interpretable. This is further exacerbated in a multilayer network since each embedding component can be designed to capture properties related to nodes, actors, edges, and/or layers. Attention should hence be devoted to advances in representation learning to develop better and more understandable embedding-based transformations of multilayer networks.

Emergence for evaluation benchmarks. Another area of improvement concerns the development of standardized evaluation benchmarks which might enable researchers and practitioners to fairly compare network simplification methods. Ultimately, this would allow us to take more robust decisions about how to choose the most appropriate method for the task at hand.

Bibliography

- M. Adler and M. Mitzenmacher. Towards compressing Web graphs. Proc. Conf. on Data Compression, pages 203–212, 2001.
- [2] Nazanin Afsarmanesh and Matteo Magnani. Finding overlapping communities in multiplex networks. CoRR, abs/1602.03746, 2016.
- [3] Brian Baingana and Georgios B. Giannakis. Centrality-constrained graph embedding. In *IEEE International Conference on Acoustics, Speech and Signal Processing, ICASSP 2013, Vancouver, BC, Canada, May 26-31, 2013*, pages 3113–3117, 2013.
- [4] Anjon Basak, Fei Fang, Thanh Hong Nguyen, and Christopher Kiekintveld. Abstraction Methods for Solving Graph-Based Security Games. pages 13–33. Springer, Cham, 2016.
- [5] Pavlos Basaras, George Iosifidis, Dimitrios Katsaros, and Leandros Tassiulas. Identifying influential spreaders in complex multilayer networks: A centrality perspective. *IEEE Trans. Network Science and Engineering*, 6(1):31–45, 2019.
- [6] F. Battiston, V. Nicosia, and V. Latora. Efficient exploration of multiplex networks. New J. Phys, 18(4):043035, 2016.

- [7] Fabian Beck, Michael Burch, Stephan Diehl, and Daniel Weiskopf. A taxonomy and survey of dynamic graph visualization. *Comput. Graph. Forum*, 36(1):133–159, 2017.
- [8] Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern* analysis and machine intelligence, 35(8):1798–1828, 2013.
- [9] M. Berlingerio, M. Coscia, and F. Giannotti. Finding and characterizing communities in multidimensional networks. In Proc. IEEE/ACM Advances in Social Network Analysis and Mining (ASONAM), pages 490– 494, 2011.
- [10] M. Berlingerio, F. Pinelli, and F. Calabrese. ABACUS: frequent pattern mining-based community discovery in multidimensional networks. *Data Min. Knowl. Discov.*, 27(3):294–320, 2013.
- [11] Michele Berlingerio, Michele Coscia, Fosca Giannotti, Anna Monreale, and Dino Pedreschi. Multidimensional networks: foundations of structural analysis. World Wide Web, 16(5-6):567–593, 2013.
- [12] I. Borg and P.J.F. Groenen. Modern Multidimensional Scaling: Theory and Applications. Springer Science & Business Media, 2005.
- [13] P. Bródka, A. Chmiel, M. Magnani, and G. Ragozini. Quantifying layer similarity in multiplex networks: a systematic study. *Royal Society open science*, 5(8), 2018.
- [14] P. Bródka, K. Skibicki, P. Kazienko, and K. Musial. A degree centrality in multi-layered social network. In Proc. Conf. on Computational Aspects of Social Networks (CASoN), pages 237–242, 2011.
- [15] T.N. Bui and C. Jones. A heuristic for reducing fill-in in sparse matrix factorization, 1993.
- [16] Aydın Buluç, Henning Meyerhenke, Ilya Safro, Peter Sanders, and Christian Schulz. Recent Advances in Graph Partitioning. pages 117–158. Springer International Publishing, 2016.
- [17] Hongyun Cai, Vincent W Zheng, and Kevin Chang. A comprehensive survey of graph embedding: problems, techniques and applications. *IEEE Transactions on Knowledge and Data Engineering*, 2018.
- [18] Shaosheng Cao, Wei Lu, and Qiongkai Xu. Deep neural networks for learning graph representations. In Proc. AAAI Conf. on Artificial Intelligence, pages 1145–1152, 2016.
- [19] V. Carchiolo, A. Longheu, M. Malgeri, and G. Mangioni. Communities unfolding in multislice networks. In *Proc. Complex Networks*, pages 187– 195, 2010.

- [20] Giona Casiraghi, Vahan Nanumyan, Ingo Scholtes, and Frank Schweitzer. From relational data to graphs: Inferring significant links using generalized hypergeometric ensembles. In Proc. Int. Conf. on Social Informatics (SocInfo), pages 111–120, 2017.
- [21] Sandro Cavallari, Vincent W. Zheng, HongYun Cai, Kevin Chen-Chuan Chang, and Erik Cambria. Learning community embedding with community detection and node embedding on graphs. In Proc. ACM Conf. on Information and Knowledge Management, pages 377–386, 2017.
- [22] T. Chakraborty and R. Narayanam. Cross-layer betweenness centrality in multiplex networks with applications. pages 397–408, 2016.
- [23] Aaron Clauset, M. E J Newman, and Cristopher Moore. Finding community structure in very large networks. *Physical Review E - Statistical*, *Nonlinear, and Soft Matter Physics*, 70(6 2), 2004.
- [24] Manlio De Domenico, Andrea Lancichinetti, Alex Arenas, and Martin Rosvall. Identifying modular flows on multilayer networks reveals highly overlapping organization in interconnected systems. *Phys. Rev.* X, 5:011027, 2015.
- [25] Manlio De Domenico, Vincenzo Nicosia, Alexandre Arenas, and Vito Latora. Structural reducibility of multilayer networks. *Nature Communications*, 6:6864, apr 2015.
- [26] Manlio De Domenico, Mason A. Porter, and Alex Arenas. Muxviz: a tool for multilayer analysis and visualization of networks. *Journal of Complex Networks*, 3(2):159–176, 2015.
- [27] Navid Dianati. Unwinding the hairball graph: Pruning algorithms for weighted complex networks. *Physical Review E*, 93:012304, 2016.
- [28] ME Dickison, Matteo Magnani, and Luca Rossi. Multilayer Social Networks. Cambridge University Press, 2016.
- [29] Cangfeng Ding and Kan Li. Centrality ranking in multiplex networks using topologically biased random walks. *Neurocomputing*, 312:263–275, 2018.
- [30] Cangfeng Ding and Kan Li. Topologically biased random walk for diffusions on multiplex networks. J. Comput. Science, 28:343–356, 2018.
- [31] Ugur Dogrusoz, Mehmet E. Belviranli, and Alptug Dilek. Cise: A circular spring embedder layout algorithm. *IEEE Trans. Vis. Comput. Graph.*, 19(6):953–966, 2013.
- [32] M. De Domenico, A. Sole, S. Gomez, and A. Arenas. Navigability of interconnected networks under random failures. *PNAS*, 111(23):8351– 8356, 2014.

- [33] Patrick Doreian, Vladimir Batagelj, and Anuška Ferligoj. Generalized blockmodeling of two-mode network data. *Social Networks*, 26(1):29 – 53, 2004.
- [34] Martin G. Everett and Steve Borgatti. Role colouring a graph. Mathematical Social Sciences, 21(2):183–188, apr 1991.
- [35] Wenfei Fan, Jianzhong Li, Xin Wang, and Yinghui Wu. Query preserving graph compression. In Proc. ACM SIGMOD Int. Conf. on Management of Data, SIGMOD '12, pages 157–168, New York, NY, USA, 2012. ACM.
- [36] Katherine Faust. Comparison of methods for positional analysis: Structural and general equivalences. *Social Networks*, 10(4):313 341, 1988.
- [37] Tomas Feder and R. Motwani. Clique Partitions, Graph Compression and Speeding-Up Algorithms. *Journal of Computer and System Sciences*, 51:261–272, 1995.
- [38] Thomas M. J. Fruchterman and Edward M. Reingold. Graph drawing by force-directed placement. Software: Practice and Experience, 21(11):1129– 1164, nov 1991.
- [39] Edoardo Galimberti, Francesco Bonchi, and Francesco Gullo. Core decomposition and densest subgraph in multilayer networks. In *Proc. ACM Conf.* on Information and Knowledge Management, pages 1807–1816, 2017.
- [40] Robert Geisberger, Peter Sanders, Dominik Schultes, and Christian Vetter. Exact Routing in Large Road Networks Using Contraction Hierarchies. *Transportation Science*, 46(3):388–404, aug 2012.
- [41] V. Gemmetto, A. Cardillo, and D. Garlaschelli. Irreducible network backbones: unbiased graph filtering via maximum entropy. arXiv, June 2017.
- [42] Minas Gjoka, Carter T. Butts, Maciej Kurant, and Athina Markopoulou. Multigraph Sampling of Online Social Networks. *IEEE Journal on Selected Areas in Communications*, 29(9):1893–1905, oct 2011.
- [43] Roland Glantz, Henning Meyerhenke, and Christian Schulz. Tree-Based Coarsening and Partitioning of Complex Networks. *Journal of Experimental Algorithmics*, 21(1):1–20, jan 2016.
- [44] Palash Goyal and Emilio Ferrara. Graph embedding techniques, applications, and performance: A survey. *Knowl.-Based Syst.*, 151:78–94, 2018.
- [45] Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks. In Proc. ACM SIGKDD Int. Conf. on Knowledge Discovery and Data Mining, pages 855–864. ACM, 2016.
- [46] A. Gupta, G. Karypis, and V. Kumar. Highly scalable parallel algorithms for sparse matrix factorization. *IEEE Transactions on Parallel and Distributed Systems*, 8(5):502–520, may 1997.

- [47] Stefan Hachul and Michael Jünger. Drawing Large Graphs with a Potential-Field-Based Multilevel Algorithm. *Graph Drawing*, 3383:285– 295, 2005.
- [48] William L. Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. In Proc. Annual Conf. on Neural Information Processing Systems, pages 1025–1035, 2017.
- [49] Yufei Han and Yun Shen. Partially supervised graph embedding for positive unlabelled feature selection. In Proc. Int. Joint Conf. on Artificial Intelligence (IJCAI), pages 1548–1554, 2016.
- [50] Keith Henderson, Brian Gallagher, Tina Eliassi-Rad, Hanghang Tong, Sugato Basu, Leman Akoglu, Danai Koutra, Christos Faloutsos, and Lei Li. Rolx: Structural role extraction & mining in large graphs. In Proc. ACM SIGKDD Int. Conf. on Knowledge Discovery and Data Mining, KDD '12, pages 1231–1239, New York, NY, USA, 2012. ACM.
- [51] Bruce Hendrickson and Robert Leland. A multilevel algorithm for partitioning graphs. In Proc. ACM/IEEE Conf. on Supercomputing, pages 28–es, New York, New York, USA, 1995. ACM Press.
- [52] Thomas Hofmann and Joachim M. Buhmann. Multidimensional scaling and data clustering. In Advances in Neural Information Processing Systems 7, [NIPS Conference, Denver, Colorado, USA, 1994], pages 459–466, 1994.
- [53] Paul W. Holland and Samuel Leinhardt. An exponential family of probability distributions for directed graphs. *Journal of the American Statistical Association*, 76(373):33–50, 1981.
- [54] Manuel Holtgrewe, Peter Sanders, and Christian Schulz. Engineering a scalable high quality graph partitioner. In 2010 IEEE International Symposium on Parallel & Distributed Processing (IPDPS), pages 1–12. IEEE, 2010.
- [55] Y. F. Hu. Efficient and high quality force-directed graph drawing. The Mathematica Journal, 10:37–71, 2005.
- [56] Roberto Interdonato, Andrea Tagarelli, Dino Ienco, Arnaud Sallaberry, and Pascal Poncelet. Local community detection in multilayer networks. *Data Min. Knowl. Discov.*, 31(5):1444–1479, 2017.
- [57] L. G. S. Jeub, M. W. Mahoney, P. J. Mucha, and M. A. Porter. A Local Perspective on Community Structure in Multilayer Networks. *Network Science*, pages 1–20, 2015.
- [58] T. Kamada and S. Kawai. An algorithm for drawing general undirected graphs. Inf. Process. Lett., 31(1):7–15, 1989.

- [59] George Karypis and Vipin Kumar. A Fast and High Quality Multilevel Scheme for Partitioning Irregular Graphs. SIAM Journal on Scientific Computing, 20(1):359–392, 1998.
- [60] Ehsan Khadangi, Alireza Bagheri, and Amin Shahmohammadi. Biased sampling from facebook multilayer activity network using learning automata. Appl. Intell., 45(3):829–849, 2016.
- [61] Kifayat Ullah Khan, Waqas Nawaz, and Young-Koo Lee. Scalable Compression of a Weighted Graph. nov 2016.
- [62] J. Kim and J.-G. Lee. Community detection in multi-layer graphs: A survey. SIGMOD Record, 44(3):37–48, 2015.
- [63] Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. arXiv preprint arXiv:1609.02907, 2016.
- [64] M. Kivela, A. Arenas, M. Barthelemy, J. P. Gleeson, Y. Moreno, and M. A. Porter. Mutilayer networks. *Journal of Complex Networks*, 2(3):203–271, 2014.
- [65] Gueorgi Kossinets. Effects of missing data in social networks. Social Networks, 28(3):247–268, 2006.
- [66] V Krishnamurthy, M Faloutsos, M Chrobak, and L Lao. Reducing Large Internet Topologies. NETWORKING 2005. Networking Technologies, Services, and Protocols; Performance of Computer and Communication Networks; Mobile and Wireless Communications Systems, pages 328–341, 2005.
- [67] Z. Kuncheva and G. Montana. Community detection in multiplex networks using locally adaptive random walks. pages 1308–1315, 2015.
- [68] Dominique LaSalle and George Karypis. Multi-threaded modularity based graph clustering using the multilevel paradigm. J. Parallel Distrib. Comput., 76:66–80, 2015.
- [69] E. O. Laumann, P. V. Marsden, and D. Prensky. The boundary specification problem in network analysis. ., pages 18–34. Sage Publications, 1983.
- [70] Sang Hoon Lee, Pan-Jun Kim, and Hawoong Jeong. Statistical properties of sampled networks. *Phys. Rev. E*, 73:016102, Jan 2006.
- [71] Jure Leskovec and Christos Faloutsos. Sampling from large graphs. In Proc. ACM SIGKDD Int. Conf. on Knowledge Discovery and Data Mining, page 631, New York, New York, USA, 2006. ACM Press.
- [72] Jure Leskovec, Jon Kleinberg, and Christos Faloutsos. Graphs over time. In Proc. ACM SIGKDD Int. Conf. on Knowledge Discovery and Data Mining, page 177, New York, New York, USA, 2005. ACM Press.

- [73] Meizhu Li, Qi Zhang, and Yong Deng. Evidential identification of influential nodes in network of networks. *Chaos, Solitons & Fractals*, 117:283– 296, 2018.
- [74] Yongsub Lim, U Kang, and Christos Faloutsos. SlashBurn: Graph Compression and Mining beyond Caveman Communities. *IEEE Transactions* on Knowledge and Data Engineering, 26(12):3077–3089, dec 2014.
- [75] Weiyi Liu, Pin-Yu Chen, Sailung Yeung, Toyotaro Suzumura, and Lingli Chen. Principled multilayer network embedding. In 2017 IEEE International Conference on Data Mining Workshops, ICDM Workshops 2017, New Orleans, LA, USA, November 18-21, 2017, pages 134–141, 2017.
- [76] Yike Liu, Tara Safavi, Abhilash Dighe, and Danai Koutra. Graph summarization methods and applications: A survey. ACM Comput. Surv., 51(3):62:1–62:34, 2018.
- [77] C. W. Loe and H. J. Jensen. Comparison of communities detection algorithms for multiplex. *Physica A*, 431:29—45, 2015.
- [78] François Lorrain and Harrison C. White. Structural equivalence of individuals in social networks. *Journal of Mathematical Sociology*, 1(1):49–80, 12 1971.
- [79] Joseph J. Luczkovich, Stephen P. Borgatti, Jeffrey C. Johnson, and Martin G. Everett. Defining and Measuring Trophic Role Similarity in Food Webs Using Regular Equivalence. *Journal of Theoretical Biology*, 220(3):303–321, 2003.
- [80] Domenico Mandaglio, Alessia Amelio, and Andrea Tagarelli. Consensus community detection in multilayer networks using parameter-free graph pruning. In Proc. Pacific-Asia Conf. on Knowledge Discovery and Data Mining (PAKDD), pages 193–205, 2018.
- [81] Sebastian Maneth and Fabian Peternek. A survey on methods and systems for graph compression. CoRR, abs/1504.00616, 2015.
- [82] Sebastian Maneth and Fabian Peternek. Grammar-based graph compression. *Information Systems*, 76:19 45, 2018.
- [83] Shawn Martin, W. Michael Brown, Richard Klavans, and Kevin W. Boyack. OpenOrd: an open-source toolbox for large graph layout. page 786806, jan 2011.
- [84] Rossana Mastrandrea, Tiziano Squartini, Giorgio Fagiolo, and Diego Garlaschelli. Enhanced reconstruction of weighted networks from strengths and degrees. *New Journal of Physics*, 16, 2014.
- [85] Ryuta Matsuno and Tsuyoshi Murata. MELL: effective embedding method for multiplex networks. In Proc. The Web Conference, pages 1261–1268, 2018.

- [86] Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. arXiv preprint arXiv:1301.3781, 2013.
- [87] Tomas Mikolov, Ilya Sutskever, Kai Chen, Gregory S. Corrado, and Jeffrey Dean. Distributed representations of words and phrases and their compositionality. In Proc. Annual Conf. on Advances in Neural Information Processing Systems, pages 3111–3119, 2013.
- [88] Tomas Mikolov, Wen-tau Yih, and Geoffrey Zweig. Linguistic regularities in continuous space word representations. In Proc. Conf. of the North American Chapter of the Association of Computational Linguistics, pages 746–751, 2013.
- [89] Jacob D. Moorman, Qinyi Chen, Thomas K. Tu, Zachary M. Boyd, and Andrea L. Bertozzi. Filtering methods for subgraph matching on multiplex networks. In *IEEE Int. Conf. on Big Data*, pages 3980–3985, 2018.
- [90] Christopher Morris, Kristian Kersting, and Petra Mutzel. Glocalized weisfeiler-lehman graph kernels: Global-local feature maps of graphs. In 2017 IEEE International Conference on Data Mining, ICDM 2017, New Orleans, LA, USA, November 18-21, 2017, pages 327–336, 2017.
- [91] Seyedeh Fatemeh Mousavi, Mehran Safayani, Abdolreza Mirzaei, and Hoda Bahonar. Hierarchical graph embedding in vector space by graph pyramid. *Pattern Recognition*, 61:245–254, 2017.
- [92] P. J. Mucha, T. Richardson, K. Macon, M. A. Porter, and J.-P. Onnela. Community structure in time-dependent, multiscale, and multiplex networks. *Science*, 328(5980):876–878, 2010.
- [93] Saket Navlakha, Rajeev Rastogi, and Nisheeth Shrivastava. Graph summarization with bounded error. In Proc. ACM SIGMOD Int. Conf. on Management of Data, page 419, New York, New York, USA, 2008. ACM Press.
- [94] M. E. J. Newman. Scientific collaboration networks. II. Shortest paths, weighted networks, and centrality. *Physical Review E*, 64(1):016132, jun 2001.
- [95] M. E J Newman and M. Girvan. Finding and evaluating community structure in networks. *Physical Review E - Statistical, Nonlinear, and* Soft Matter Physics, 69(2 2):026113, feb 2004.
- [96] Mathias Niepert, Mohamed Ahmed, and Konstantin Kutzkov. Learning convolutional neural networks for graphs. In Proc. Int. Conf. on Machine Learning (ICML), pages 2014–2023, 2016.

- [97] Farshad Nourbakhsh, Samuel Rota Bulo, and Marcello Pelillo. A Matrix Factorization Approach to Graph Compression. In 2014 22nd International Conference on Pattern Recognition, pages 76–81. IEEE, aug 2014.
- [98] Tore Opsahl. Triadic closure in two-mode networks: Redefining the global and local clustering coefficients. *Social Networks*, 35(2):159–167, may 2013.
- [99] Vitaly Osipov and Peter Sanders. n-Level Graph Partitioning. pages 278–289. Springer, Berlin, Heidelberg, 2010.
- [100] Benigno Padrón, Manuel Nogales, and Anna Traveset. Alternative approaches of transforming bimodal into unimodal mutualistic networks. The usefulness of preserving weighted information. *Basic and Applied Ecology*, 12(8):713–721, 2011.
- [101] A Roxana Pamfil, Sam D Howison, Renaud Lambiotte, and Mason A Porter. Relating modularity maximization and stochastic block models in multilayer networks. arXiv preprint arXiv:1804.01964, 2018.
- [102] Achilleas Papakostas and Ioannis G. Tollis. Algorithms for area-efficient orthogonal drawings. *Comput. Geom.*, 9(1-2):83–110, 1998.
- [103] E. E. Papalexakis, L. Akoglu, and D. Ienco. Do more views of a graph help? community detection and clustering in multi-graphs. In Proc. Int. Conf. on Information Fusion, pages 899–905, 2013.
- [104] Panos Parchas, Francesco Gullo, Dimitris Papadias, and Francesco Bonchi. Uncertain graph processing through representative instances. ACM Trans. Database Syst., 40(3):20:1–20:39, 2015.
- [105] Subhadeep Paul, Yuguo Chen, et al. Consistent community detection in multi-relational data through restricted multi-layer stochastic blockmodel. *Electronic Journal of Statistics*, 10(2):3807–3870, 2016.
- [106] Tiago P Peixoto. Bayesian stochastic blockmodeling. arXiv preprint arXiv:1705.10225, 2017.
- [107] Tiago P Peixoto. Nonparametric weighted stochastic block models. *Phys-ical Review E*, 97(1):012306, 2018.
- [108] Diego Perna, Roberto Interdonato, and Andrea Tagarelli. Identifying users with alternate behaviors of lurking and active participation in multilayer social networks. *IEEE Trans. Comput. Social Systems*, 5(1):46–63, 2018.
- [109] Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: Online learning of social representations. In Proc. ACM SIGKDD Int. Conf. on Knowledge Discovery and Data Mining, pages 701–710. ACM, 2014.

- [110] Filippo Radicchi, Jose J. Ramasco, and Santo Fortunato. Information filtering in complex weighted networks. *Physical Review E*, 83:046101, 2011.
- [111] Davood Rafiei and Stephen Curial. Effectively visualizing large networks through sampling. In Proc. of the IEEE Visualization Conference, page 48, 2005.
- [112] Alireza Rezvanian, Mohammad Rahmati, and Mohammad Reza Meybodi. Sampling from complex networks using distributed learning automata. *Physica A: Statistical Mechanics and its Applications*, 396:224 – 234, 2014.
- [113] J. Rissanen. Modeling by shortest data description. Automatica, 14(5):465 - 471, 1978.
- [114] Luca Rossi and Matteo Magnani. Towards effective visual analytics on multiplex and multilayer networks. *Chaos, Solitons & Fractals*, 72:68–76, mar 2015.
- [115] Ryan A. Rossi and Nesreen K. Ahmed. Role discovery in networks. IEEE Transactions on Knowledge and Data Engineering, 27(4):1112–1131, 4 2015.
- [116] Ilya Safro, Peter Sanders, and Christian Schulz. Advanced Coarsening Schemes for Graph Partitioning. *Journal of Experimental Algorithmics*, 19:1.1–1.24, jan 2015.
- [117] Peter Sanders and Christian Schulz. Engineering multilevel graph partitioning algorithms. In Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics), volume 6942 LNCS, pages 469–480. Springer, Berlin, Heidelberg, 2011.
- [118] Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The graph neural network model. *IEEE Transactions on Neural Networks*, 20(1):61–80, 2009.
- [119] Stephen B. Seidman. Network structure and minimum degree. Social Networks, 5(3):269–287, 1983.
- [120] Cathrine Seierstad and Tore Opsahl. For the few not the many? The effects of affirmative action on presence, prominence, and social capital of women directors in Norway. *Scandinavian Journal of Management*, 27(1):44–54, mar 2011.
- [121] M. Ángeles Serrano, Marián Boguñá, and Alessandro Vespignani. Extracting the multiscale backbone of complex weighted networks. Proc. of the National Academy of Sciences, 106(16):6483–6488, 2009.

- [122] Neil Shah, Danai Koutra, Tianmin Zou, Brian Gallagher, and Christos Faloutsos. TimeCrunch: Interpretable Dynamic Graph Summarization. In Proc. ACM SIGKDD Int. Conf. on Knowledge Discovery and Data Mining, KDD '15, pages 1055–1064, New York, NY, USA, 2015. ACM.
- [123] A. Solé-Ribalta, M. De Domenico, S. Gómez, and A. Arenas. Centrality rankings in multiplex networks. In Proc. ACM Conf. on Web Science (WebSci), pages 149–155, 2014.
- [124] Albert Solé-Ribalta, Manlio De Domenico, Sergio Gómez, and Alex Arenas. Random walk centrality in interconnected multilayer networks. *Phys*ica D: Nonlinear Phenomena, 323:73–79, 2016.
- [125] Tiziano Squartini, Rossana Mastrandrea, and Diego Garlaschelli. Unbiased sampling of network ensembles. New Journal of Physics, 17:023052, 2015.
- [126] N. Stanley, S. Shai, D. Taylor, and P. J. Mucha. Clustering network layers with the strata multilayer stochastic block model. *IEEE Transactions on Network Science and Engineering*, 3(2):95–105, April 2016.
- [127] Michael P H Stumpf, Carsten Wiuf, and Robert M May. Subnets of scale-free networks are not scale-free: sampling properties of networks. Proc. of the National Academy of Sciences of the United States of America, 102(12):4221-4, mar 2005.
- [128] Jian Tang, Meng Qu, Mingzhe Wang, Ming Zhang, Jun Yan, and Qiaozhu Mei. LINE: large-scale information network embedding. In Proc. Int. Conf. on World Wide Web, pages 1067–1077, 2015.
- [129] L. Tang, X. Wang, and H. Liu. Uncoverning groups via heterogeneous interaction analysis. In Proc. IEEE Int. Conf. on Data Mining (ICDM), pages 503–512. IEEE, 2009.
- [130] L. Tang, X. Wang, and H. Liu. Community detection via heterogeneous interaction analysis. *Data Min. Knowl. Discov.*, 25:1–33, 2012.
- [131] S. Tavassoli and K. A. Zweig. Most central or least central? how much modeling decisions influence a node's centrality ranking in multiplex networks. In Proc. European Network Intelligence Conf. (ENIC), pages 25– 32, 2016.
- [132] Fei Tian, Bin Gao, Qing Cui, Enhong Chen, and Tie-Yan Liu. Learning deep representations for graph clustering. In Proc. AAAI Conf. on Artificial Intelligence, pages 1293–1299, 2014.
- [133] Hannu Toivonen, Fang Zhou, Aleksi Hartikainen, and Atte Hinkka. Compression of weighted graphs. In Proc. ACM SIGKDD Int. Conf. on Knowledge Discovery and Data Mining, page 965, New York, New York, USA, 2011. ACM Press.

- [134] Chris Walshaw. A Multilevel Algorithm for Force-Directed Graph-Drawing. Journal of Graph Algorithms and Applications, 7(3):253–285, 2003.
- [135] Daixin Wang, Peng Cui, and Wenwu Zhu. Structural deep network embedding. In Proc. ACM SIGKDD Int. Conf. on Knowledge Discovery and Data Mining, pages 1225–1234. ACM, 2016.
- [136] Dingjie Wang and Xiufen Zou. A new centrality measure of nodes in multilayer networks under the framework of tensor computation. *Applied Mathematical Modelling*, 54:46–63, 2018.
- [137] Xiao Wang, Peng Cui, Jing Wang, Jian Pei, Wenwu Zhu, and Shiqiang Yang. Community preserving network embedding. In Proc. AAAI Conf. on Artificial Intelligence, pages 203–209, 2017.
- [138] Stanley Wasserman and Katherine Faust. Social network analysis: methods and applications. Cambridge University Press, 1994.
- [139] Ming Yin, Junbin Gao, and Zhouchen Lin. Laplacian regularized low-rank representation and its applications. *IEEE Trans. Pattern Anal. Mach. Intell.*, 38(3):504–517, 2016.
- [140] Hongming Zhang, Liwei Qiu, Lingling Yi, and Yangqiu Song. Scalable multiplex network embedding. In Proc. Int. Joint Conf. on Artificial Intelligence (IJCAI), pages 3082–3088, 2018.
- [141] Na Zhao, Hanwang Zhang, Meng Wang, Richang Hong, and Tat-Seng Chua. Learning content-social influential features for influence analysis. *IJMIR*, 5(3):137–149, 2016.
- [142] Aleš Ziberna. Blockmodeling of multilevel networks. Social Networks, 39:46–61, 2014.